



RECIPROCATING SAWS

SAWZALL® - THE HATCHET® RECIPROCATING SAW

6524-21
0-3,000 SPM
WITH CASE



FEATURES:

- 6 position pivoting handle.
- Compact and only 6.7 lbs.
- Quik-Lok™ blade clamp.
- 0-3,000 SPM, 3/4 in. stroke length.
- Orbital cutting action.
- 7.5 amp Milwaukee built motor.
- Gear protecting clutch.
- Keyless adjustable shoe.
- Cushion grip and rubber boot for superior gripping.
- Heavy-duty 'S' Jacket 8 ft. two-wire Quik-Lok® removable cord.
- Double insulated.
- Uses standard 1/2 in. tang reciprocating saw blades.
- Blades may be clamped upside down.
- Impact resistant carrying case.

SPECIFICATIONS

Voltage	120 AC
Amps	7.5
Stroke Length	3/4 in.
Cord Type	10 ft. Quik-Lok
Construction Type	Double Insulated
Switch Type	Trigger
Dial Speed Control	No
Keyless Blade Clamp	Yes
Keyless Adjustable Shoe	Yes
Adjustable Handle	Yes
Orbital Action	Yes
Counter-Balance	Yes
Impact Protection	No
Length	13-1/2 in. / 19-1/2 in.
Weight	6.7 lbs.

MILWAUKEE 10 AMP SAWZALL® RECIPROCATING SAW

6509-20
0-2,800 SPM



FEATURES:

- 10 amp Milwaukee built motor.
- 1-2,800 SPM variable speed trigger.
- Quik-Lok™ blade clamp for fast, easy blade changes.
- Double bearing wobble plate mechanism for less vibration.
- Center picot adjustable shoe.
- Rubber boot for superior gripping.
- 2 Super Sawzall® blades
- Heavy-duty 'S' Jacket 8 ft. two-wire rubber cord.
- Double insulated.
- Uses standard 1/2 in. shank Sawzall® Blades – blades may be clamped upside down for special cutting needs.

INCLUDES

2 Super Sawzall® blades

SPECIFICATIONS

Voltage	120 AC
Amps	10.0
Stroke Length	3/4 in.
Cord Type	8 ft. Fixed
Switch Type	Trigger
Dial Speed Control	No
Keyless Blade Clamp	No
Keyless Adjustable Shoe	Yes
Adjustable Handle	No
Orbital Action	No
Counter-Balance	No
Impact Protection	No
Length	17-1/3 in.
Weight	7 lbs.

360° ROTATING HANDLE ORBITAL SUPER SAWZALL® RECIPROCATING SAW

6523-21
0-3,000 SPM
WITH CASE



FEATURES:

- 360° rotating handle.
- 13 amp Milwaukee built motor.
- Orbital cutting action.
- Variable speed trigger, 0-3,000 SPM.
- 1-1/4 in. stroke.
- Counter balanced/gear protection system.
- Speed dial.
- Quik-Lok™ blade clamp.
- Quik-Lok® cord.
- 2 Super Sawzall® blades

INCLUDES

2 Super Sawzall® blades



Heavy-duty, blow molded polyethylene construction.

SPECIFICATIONS

Voltage	120 AC/DC
Amps	13.0
Stroke Length	1-1/4 in.
Cord Type	10 ft. Quik-Lok
Construction Type	Double Insulated
Switch Type	Trigger
Dial Speed Control	Yes
Keyless Blade Clamp	Yes
Keyless Adjustable Shoe	Yes
Adjustable Handle	Yes
Orbital Action	Yes
Counter-Balance	Yes
Impact Protection	Yes
Length	19 in.
Weight	10 lbs.

