

7 IN. / 9 IN. SANDERS

6066-6

3.5 Max. HP
15 AMPS
6,000 RPM

FEATURES:

- Spiral bevel gearing for performance and durability.
- Sander may be converted to grinder by using the proper wheel guard.



SPECIFICATIONS

Voltage 120 AC/DC
Spindle 5/8 in.-11
Cord Type 9 ft. Fixed
Construction Type Grounded
Switch Type Trigger
Trigger Lock On
Spindle Lock Yes
Adjustable Handle No
Electronic Feedback No
Length 17-1/2 in.
Weight 12 lbs.

6072

2.25 Max. HP
13 AMPS
5,000 RPM

FEATURES:

- Spiral bevel gearing for performance and durability.
- Sander may be converted to grinder by using the proper wheel guard.



SPECIFICATIONS

Voltage 120 AC/DC
Spindle 5/8 in.-11
Cord Type 9 ft. Fixed
Construction Type Double Insulated
Switch Type Trigger
Trigger Lock On
Spindle Lock Yes
Adjustable Handle No
Electronic Feedback No
Length 17 in.
Weight 9.3 lbs.

6078

2.25 Max. HP
13 AMPS
0-6,000 RPM

FEATURES:

- Dial speed control 0-6,000 RPM.
- 10 ft., 2-wire Quik-Lok® cord set.



SPECIFICATIONS

Voltage 120 AC Only
Spindle 5/8 in.-11
Cord Type 10 ft. Quik-Lok
Construction Type Double Insulated
Switch Type Trigger
Trigger Lock On
Spindle Lock Yes
Adjustable Handle No
Electronic Feedback No
Length 17 in.
Weight 9.3 lbs.

ALL INCLUDE

Side handle
Flange and nylon washer

ACCESSORIES

Carrying Case for 13 & 15 AMP Sanders and Grinders



FEATURES:

- 20-gauge steel with baked enamel paint to resist rust.
- Ideal for tool and accessory storage.
- Steel clasps for positive closure.



Sanding Disc

Spiral Backing Pad