



HEAT GUN / CAULK GUN

HEAT GUNS

8975-6

Dual Temperature
570°F and 1000°F
11.6 AMPS

8985 (Kit)

Variable Temperature
140°F - 1040°F
11.6 AMPS

FEATURES:

- Unique impact resistant heating element.
- Efficient soft air velocity increases surface temperature much faster than conventional hot air heat guns.
- Three position rocker switch – off, high and low (8975-6).
- Rotate rear housing to select temperature (8985).



SPECIFICATIONS

Voltage 120 AC
Amps 11.6
Air Temperatures 570°F/1,000°F
Air Volume 14.8 cu. ft./min.
Length 10-1/8 in.
Weight 1.6 lbs.



8985 INCLUDES

Carrying case
Accessory assortment

ACCESSORIES

Deflector
Nozzle



Air
Reducer
Nozzle



CAULK GUN

With 10 oz. Carriage Kit

6560-21

12 VOLT
Cordless

FEATURES:

- Dramatically reduces user fatigue when compared to manual application.
- Expels over 135 (10 oz.) tubes of latex per battery charge.
- 620 pounds of pushing force easily handles high viscosity materials such as windshield urethanes.
- Variable speed switch for better flow control.



6560-21 SPECIFICATIONS

Voltage 12 DC
Carriage 10 oz.
Force 620 lbs.
Reversible Battery Yes
No. of Batteries Included 1
Amp Hours 1.3
Trigger Lock Off
Length 18-1/2 in.
Weight 5.2 lbs.

INCLUDES

10 oz. carriage
Plunger rod
Battery
Charger

COMMON APPLICATIONS

- Auto glass repair and installations
- Weather-stripping
- Fire-stopping
- Sealing plumbing fixtures
- Concrete repair
- Water proofing
- Sound proofing

ACCESSORIES



Quart Size Caulk Cartridge



Plunger Rod for 20 oz.
Caulk Carriage
Sausage Style



One-Hour NiCd DC Charger
(Charges all Milwaukee Power Plus Batteries)