

Order Guide

2nd Edition

**Mechanical and
Adhesive Anchors for
Masonry, Concrete
and Drywall**

***We didn't build the USA,
but we do hold it together!™***

Two Proven Product Lines – Now Together!
Over 100 Years of Fastening Experience

TOGGLER®
HIGH-PERFORMANCE ANCHORS®

wej-it®
HIGH-PERFORMANCE ANCHORS



Since its inception in 1968, TOGGLER Anchor System, division of Mechanical Plastics Corp., has continued to invent, improve, manufacture and sell only TOGGLER® brand anchors, the highest quality, best-performing anchors on the market. All are designed to solve real problems on the job site and at home.

Wej-It®, the original wedge anchor, first came on the scene over 62 years ago. Wej-It High-Performance Anchors is now the newest division of Mechanical Plastics Corp.

This means the proven reliability of Wej-It products is combined with the high level of customer service and support that has been provided to TOGGLER customers for over 47 years.

Investment in updated processes and technology will ensure the best quality concrete anchoring systems available to meet your high-strength concrete anchoring needs now and in the future.

We didn't build the USA, but we do hold it together!™

call us:
(203) 857-2200

Fax: 203-857-2201 • E-mail: info@toggler.com
www.toggler.com • www.wejit.com

Divisions of Mechanical Plastics Corp.
110 Richards Avenue • Norwalk, CT 06854

Table of Contents

Expansion Anchors

Ankr-TITE® Wedge Anchors	4
Ankr-TITE® CCAT Wedge Anchors	9
Original Wej-It® Wedge Anchors	10
Sleeve-TITE™ Sleeve Anchors	11

Threaded Anchors

POWER-Skru™ Large Diameter Concrete Screws	14
Wej-Con® Concrete Screws.....	16
Hang-TITE™ Rod Hanger Screws.....	19

Drop-In and Shield Anchors

Ultra-Drop™ Drop-In Anchors	21
Hollo Set™ Drop-In Anchors.....	23
POWER-Drop™ Drop-In Anchors	24
Expansion Shields	25
Lag Screw Shields	26
Machine Screw Shields.....	27

Drive Nail Anchors

Strike-It™ Center Pin Drive Anchors	28
Nail-It™ Drive Nail Anchors.....	29
Screw-In™ Drive Screw Anchors	30
Slam-It™ Split Drive Anchors.....	31
Pound-It™ Drive Anchors	32

Wall Anchors

SNAPTOGGLE® Heavy-Duty Toggle Bolts	34
SnapSkru® Self-Drilling Drywall Anchors	36
ALLIGATOR® All-Purpose Anchors	37
TOGGLER® Plastic Toggle Anchors.....	39
TOGGLER® Specialty Anchors.....	41
TOGGLER® Combo Kits.....	43
Standard Wing Toggles.....	44
Hollow Wall Anchors.....	45
Self-Drilling Drywall Anchors	46

Drill Bits

SDS-plus® Carbide-Tipped Drill Bits	47
SDS-max® Cutter Carbide-Tipped Drill Bits	48
Hex Driver and Taper Carbide-Tipped Drill Bits	49
Spline Carbide-Tipped Drill Bits.....	49

Adhesive Anchors

POWER-Sert™ Adhesive Insert Anchors	50
Inject-TITE™ (AWF) All-Weather Formula.....	51
Inject-TITE™ (FS) Fast-Set Formula	52
Inject-TITE™ (ST) Standard-Set Formula.....	53
Adhesive Accessories.....	54

Alphabetical Product Code Listing.....56

Ankr-TITE® Wedge Anchors

This anchor is a high-strength, fully threaded, and torque-controlled expansion anchor designed for anchoring into normal-weight concrete, lightweight concrete, and grouted concrete masonry. The Ankr-TITE anchor has a unique machine lathed expansion cone that supports a thick three-dimple clip engineered to provide high load carrying capability and reduce slip in a variety of installation conditions. Full product line available in all materials.

MIAMI-DADE COUNTY
APPROVED

NOA: #13-0701.05

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry

Materials

- ▶ Zinc-Plated Carbon Steel
- ▶ Hot-Dip Galvanized
- ▶ Type 304 Stainless Steel
- ▶ Type 316 Stainless Steel

**Zinc-Plated Carbon Steel**

Catalog No.	Anchor Size (in.)	Min. Embed. (in.)	Thread Length (in.)	Box Quantity	Carton Quantity
AT1413	1/4 x 1-3/4	1-1/4	3/4	100	800
AT1421	1/4 x 2-1/4	1-1/4	1-1/4	100	800
AT1431	1/4 x 3-1/4	1-1/4	2-1/4	100	800
AT3821	3/8 x 2-1/4	1-3/4	1	50	400
AT3823	3/8 x 2-3/4	1-3/4	1-1/2	50	400
AT3830	3/8 x 3	1-3/4	1-3/4	50	400
AT3833	3/8 x 3-3/4	1-3/4	2-1/2	50	400
AT3850	3/8 x 5	1-3/4	3-1/4	50	400
AT3870	3/8 x 7	1-3/4	4-1/2	50	300
AT1223	1/2 x 2-3/4	2-1/8	1-1/8	25	200
AT1233	1/2 x 3-3/4	2-1/8	2-1/8	25	200
AT1241	1/2 x 4-1/4	2-1/8	2-5/8	25	200
AT1242	1/2 x 4-1/2	2-1/8	2-5/8	25	200
AT1252	1/2 x 5-1/2	2-1/8	3-3/4	25	150
AT1270	1/2 x 7	2-1/8	4-1/2	25	150
AT1282	1/2 x 8-1/2	2-1/8	5	10	40
AT1210	1/2 x 10	2-1/8	5	10	40
AT5832	5/8 x 3-1/2	2-5/8	1-1/2	10	80
AT5841	5/8 x 4-1/4	2-5/8	2-3/8	10	80
AT5842*	5/8 x 4-1/2	2-5/8	2-5/8	10	80
AT5850	5/8 x 5	2-5/8	3-1/8	10	80
AT5860	5/8 x 6	2-5/8	4	10	80
AT5870	5/8 x 7	2-5/8	4-1/2	10	80
AT5882	5/8 x 8-1/2	2-5/8	5	10	40
AT5810	5/8 x 10	2-5/8	5	10	40
AT5812	5/8 x 12	2-5/8	5	10	40

continues on page 5

* Special Order

Ankr-TITE[®] Wedge Anchors

Zinc-Plated Carbon Steel

continued from page 4

Catalog No.	Anchor Size (in.)	Min. Embed. (in.)	Thread Length (in.)	Box Quantity	Carton Quantity
AT3441	3/4 x 4-1/4	3-1/4	2	10	80
AT3443	3/4 x 4-3/4	3-1/4	2-1/2	10	80
AT3452	3/4 x 5-1/2	3-1/4	3-1/4	10	60
AT3461	3/4 x 6-1/4	3-1/4	3-3/4	10	60
AT3470	3/4 x 7	3-1/4	4-3/4	10	60
AT3482	3/4 x 8-1/2	3-1/4	5	10	40
AT3410	3/4 x 10	3-1/4	5	10	40
AT3412	3/4 x 12	3-1/4	5	5	20
AT7860	7/8 x 6	3-7/8	3-1/2	5	30
AT7880	7/8 x 8	3-7/8	5	5	20
AT7810	7/8 x 10	3-7/8	5	5	20
AT1060	1 x 6	4	3	5	30
AT1090	1 x 9	4	5	5	20
AT1012	1 x 12	4	5	5	20
AT11490	1-1/4 x 9	5-5/8	5	4	12
AT11412	1-1/4 x 12	5-5/8	5	4	12



Tie-Wire Wedge Anchors: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Min. Embed. (in.)	Eye Dia. (in.)	Box Quantity	Carton Quantity
WTW1421	1/4 x 2-1/4	1-1/4	9/32	100	1000

Ankr-TITE® Wedge Anchors



Hot-Dip Galvanized Steel with 304 SS Clip

Catalog No.	Anchor Size (in.)	Min. Embed. (in.)	Thread Length (in.)	Box Quantity	Carton Quantity
ATG1413	1/4 x 1-3/4	1-1/4	3/4	100	800
ATG1421	1/4 x 2-1/4	1-1/4	1-1/4	100	800
ATG1431	1/4 x 3-1/4	1-1/4	2-1/4	100	800
ATG3821	3/8 x 2-1/4	1-3/4	1	50	400
ATG3823	3/8 x 2-3/4	1-3/4	1-1/2	50	400
ATG3830	3/8 x 3	1-3/4	1-3/4	50	400
ATG3833	3/8 x 3-3/4	1-3/4	2-1/2	50	400
ATG3850	3/8 x 5	1-3/4	3-1/4	50	400
ATG3870	3/8 x 7	1-3/4	4-1/2	50	300
ATG1223	1/2 x 2-3/4	2-1/8	1-1/8	25	200
ATG1233	1/2 x 3-3/4	2-1/8	2-1/8	25	200
ATG1241	1/2 x 4-1/4	2-1/8	2-5/8	25	200
ATG1242*	1/2 x 4-1/2	2-1/8	2-5/8	25	200
ATG1252	1/2 x 5-1/2	2-1/8	3-3/4	25	150
ATG1270	1/2 x 7	2-1/8	4-1/2	25	150
ATG1282	1/2 x 8-1/2	2-1/8	5	10	40
ATG1210	1/2 x 10	2-1/8	5	10	40
ATG5832	5/8 x 3-1/2	2-5/8	1-1/2	10	80
ATG5841	5/8 x 4-1/4	2-5/8	2-3/8	10	80
ATG5842	5/8 x 4-1/2	2-5/8	2-5/8	10	80
ATG5850	5/8 x 5	2-5/8	3-1/8	10	80
ATG5860	5/8 x 6	2-5/8	4	10	80
ATG5870	5/8 x 7	2-5/8	4-1/2	10	80
ATG5882	5/8 x 8-1/2	2-5/8	5	10	40
ATG5810	5/8 x 10	2-5/8	5	10	40
ATG5812	5/8 x 12	2-5/8	5	10	40
ATG3441	3/4 x 4-1/4	3-1/4	2	10	80
ATG3443	3/4 x 4-3/4	3-1/4	2-1/2	10	80
ATG3452	3/4 x 5-1/2	3-1/4	3-1/4	10	60
ATG3461	3/4 x 6-1/4	3-1/4	3-3/4	10	60
ATG3470	3/4 x 7	3-1/4	4-3/4	10	60
ATG3482	3/4 x 8-1/2	3-1/4	5	10	40
ATG3410	3/4 x 10	3-1/4	5	10	40
ATG3412	3/4 x 12	3-1/4	5	4	16
ATG7860	7/8 x 6	3-7/8	3-1/2	4	24
ATG7880	7/8 x 8	3-7/8	5	4	16
ATG7810	7/8 x 10	3-7/8	5	4	16
ATG1060	1 x 6	4	3	4	24
ATG1090	1 x 9	4	5	4	16
ATG1012	1 x 12	4	5	4	16
ATG11490	1-1/4 x 9	5-5/8	5	4	12
ATG11412	1-1/4 x 12	5-5/8	5	4	12

* Special Order

Ankr-TITE® Wedge Anchors



Type 304 Stainless Steel

Catalog No.	Anchor Size (in.)	Min. Embed. (in.)	Thread Length (in.)	Box Quantity	Carton Quantity
ATS1413	1/4 x 1-3/4	1-1/4	3/4	100	800
ATS1421	1/4 x 2-1/4	1-1/4	1-1/4	100	800
ATS1431	1/4 x 3-1/4	1-1/4	2-1/4	100	800
ATS3821	3/8 x 2-1/4	1-3/4	1	50	400
ATS3823	3/8 x 2-3/4	1-3/4	1-1/2	50	400
ATS3830	3/8 x 3	1-3/4	1-3/4	50	400
ATS3833	3/8 x 3-3/4	1-3/4	2-1/2	50	400
ATS3850	3/8 x 5	1-3/4	3-1/4	50	400
ATS3870	3/8 x 7	1-3/4	4-1/2	50	300
ATS1223	1/2 x 2-3/4	2-1/8	1-1/8	25	200
ATS1233	1/2 x 3-3/4	2-1/8	2-1/8	25	200
ATS1241	1/2 x 4-1/4	2-1/8	2-5/8	25	200
ATS1242	1/2 x 4-1/2	2-1/8	2-5/8	25	200
ATS1252	1/2 x 5-1/2	2-1/8	3-3/4	25	150
ATS1270	1/2 x 7	2-1/8	4-1/2	25	150
ATS1282	1/2 x 8-1/2	2-1/8	5	10	40
ATS1210	1/2 x 10	2-1/8	5	10	40
ATS5832	5/8 x 3-1/2	2-5/8	1-1/2	10	80
ATS5841	5/8 x 4-1/4	2-5/8	2-3/8	10	80
ATS5842*	5/8 x 4-1/2	2-5/8	2-5/8	10	80
ATS5850	5/8 x 5	2-5/8	3-1/8	10	80
ATS5860	5/8 x 6	2-5/8	4	10	80
ATS5870	5/8 x 7	2-5/8	4-1/2	10	80
ATS5882	5/8 x 8-1/2	2-5/8	5	10	40
ATS5810	5/8 x 10	2-5/8	5	10	40
ATS5812	5/8 x 12	2-5/8	5	10	40
ATS3441	3/4 x 4-1/4	3-1/4	2	10	80
ATS3443	3/4 x 4-3/4	3-1/4	2-1/2	10	80
ATS3452	3/4 x 5-1/2	3-1/4	3-1/4	10	60
ATS3461	3/4 x 6-1/4	3-1/4	3-3/4	10	60
ATS3470	3/4 x 7	3-1/4	4-3/4	10	60
ATS3482	3/4 x 8-1/2	3-1/4	5	10	40
ATS3410	3/4 x 10	3-1/4	5	10	40
ATS3412	3/4 x 12	3-1/4	5	5	20
ATS7860	7/8 x 6	3-7/8	3-1/2	5	30
ATS7880	7/8 x 8	3-7/8	5	5	20
ATS7810	7/8 x 10	3-7/8	5	5	20
ATS1060	1 x 6	4	3	5	30
ATS1090	1 x 9	4	5	5	20
ATS1012	1 x 12	4	5	5	20
ATS11490*	1-1/4 x 9	5-5/8	5	4	12
ATS11412*	1-1/4 x 12	5-5/8	5	4	12

* Special Order

Ankr-TITE® Wedge Anchors



Type 316 Stainless Steel

Catalog No.	Anchor Size (in.)	Min. Embed. (in.)	Thread Length (in.)	Box Quantity	Carton Quantity
ATSS1413	1/4 x 1-3/4	1-1/4	3/4	100	800
ATSS1421	1/4 x 2-1/4	1-1/4	1-1/4	100	800
ATSS1431	1/4 x 3-1/4	1-1/4	2-1/4	100	800
ATSS3821	3/8 x 2-1/4	1-3/4	1	50	400
ATSS3823	3/8 x 2-3/4	1-3/4	1-1/2	50	400
ATSS3830	3/8 x 3	1-3/4	1-3/4	50	400
ATSS3833	3/8 x 3-3/4	1-3/4	2-1/2	50	400
ATSS3850	3/8 x 5	1-3/4	3-1/4	50	400
ATSS3870	3/8 x 7	1-3/4	4-1/2	50	300
ATSS1223	1/2 x 2-3/4	2-1/8	1-1/8	25	200
ATSS1233	1/2 x 3-3/4	2-1/8	2-1/8	25	200
ATSS1241	1/2 x 4-1/4	2-1/8	2-5/8	25	200
ATSS1242*	1/2 x 4-1/2	2-1/8	2-5/8	25	200
ATSS1252	1/2 x 5-1/2	2-1/8	3-3/4	25	150
ATSS1270	1/2 x 7	2-1/8	4-1/2	25	150
ATSS1282	1/2 x 8-1/2	2-1/8	5	10	40
ATSS1210	1/2 x 10	2-1/8	5	10	40
ATSS5832	5/8 x 3-1/2	2-5/8	1-1/2	10	80
ATSS5841	5/8 x 4-1/4	2-5/8	2-3/8	10	80
ATSS5842*	5/8 x 4-1/2	2-5/8	2-5/8	10	80
ATSS5850	5/8 x 5	2-5/8	3-1/8	10	80
ATSS5860	5/8 x 6	2-5/8	4	10	80
ATSS5870	5/8 x 7	2-5/8	4-1/2	10	80
ATSS5882	5/8 x 8-1/2	2-5/8	5	10	40
ATSS5810	5/8 x 10	2-5/8	5	10	40
ATSS5812	5/8 x 12	2-5/8	5	10	40
ATSS3441	3/4 x 4-1/4	3-1/4	2	10	80
ATSS3443	3/4 x 4-3/4	3-1/4	2-1/2	10	80
ATSS3452	3/4 x 5-1/2	3-1/4	3-1/4	10	60
ATSS3461	3/4 x 6-1/4	3-1/4	3-3/4	10	60
ATSS3470	3/4 x 7	3-1/4	4-3/4	10	60
ATSS3482	3/4 x 8-1/2	3-1/4	5	10	40
ATSS3410	3/4 x 10	3-1/4	5	10	40
ATSS3412	3/4 x 12	3-1/4	5	5	20
ATSS7860	7/8 x 6	3-7/8	3-1/2	5	30
ATSS7880	7/8 x 8	3-7/8	5	5	20
ATSS7810	7/8 x 10	3-7/8	5	5	20
ATSS1060	1 x 6	4	3	5	30
ATSS1090	1 x 9	4	5	5	20
ATSS1012	1 x 12	4	5	5	20
ATSS11490*	1-1/4 x 9	5-5/8	5	4	12
ATSS11412*	1-1/4 x 12	5-5/8	5	4	12

* Special Order

Ankr-TITE® CCAT Wedge Anchors

This anchor is a high-strength, fully threaded, and torque-controlled expansion anchor engineered for superior performance in cracked concrete in seismic and wind load conditions. Ankr-TITE CCAT anchors meet **Category 1** design criteria. A unique safety shoulder supports the 316 stainless steel clip. 3/8" for uncracked concrete only.



ICC-ES ESR-2777
Category 1

City of Los Angeles
COLA RR 24939

Applications

- ▶ Cracked Concrete
- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry

Materials

- ▶ Zinc-Plated Carbon Steel with Type 316 Stainless Steel Clip



Cracked Concrete Wedge Anchor: Zinc-Plated Carbon Steel with 316 SS Clip

Catalog No.	Anchor Size (in.)	Thread Length (in.)	Box Quantity	Carton Quantity
CCAT3830	3/8 x 3	1-3/4	50	400
CCAT3833	3/8 x 3-3/4	2-1/2	50	400
CCAT3850	3/8 x 5	3-1/4	50	400
CCAT3870	3/8 x 7	4-1/2	50	300
CCAT1223	1/2 x 2-3/4	1-1/8	25	200
CCAT1233	1/2 x 3-3/4	2-1/8	25	200
CCAT1241	1/2 x 4-1/4	2-5/8	25	200
CCAT1242*	1/2 x 4-1/2	2-5/8	25	200
CCAT1252	1/2 x 5-1/2	3-3/4	25	150
CCAT1270	1/2 x 7	4-1/2	25	150
CCAT1282	1/2 x 8-1/2	5	10	40
CCAT1210	1/2 x 10	5	10	40
CCAT5832	5/8 x 3-1/2	1-1/2	10	80
CCAT5841	5/8 x 4-1/4	2-3/8	10	80
CCAT5850	5/8 x 5	3-1/8	10	80
CCAT5860	5/8 x 6	4	10	80
CCAT5870	5/8 x 7	4-1/2	10	80
CCAT5882	5/8 x 8-1/2	5	10	40
CCAT5810	5/8 x 10	5	10	40
CCAT3443	3/4 x 4-3/4	2-1/4	10	80
CCAT3452	3/4 x 5-1/2	3-1/4	10	60
CCAT3461	3/4 x 6-1/4	3-3/4	10	60
CCAT3470	3/4 x 7	4-3/4	10	60
CCAT3482	3/4 x 8-1/2	5	10	40
CCAT3410	3/4 x 10	5	10	40
CCAT3412*	3/4 x 12	5	5	20
CCAT1060*	1 x 6	3	5	30
CCAT1090*	1 x 9	5	5	20
CCAT1012*	1 x 12	5	5	20

* Special Order

The Original Wej-It® Wedge Anchors

This anchor has been an industry standard for over 62 years. The Original Wej-It anchors provide "positive wedge connections" to minimize wedge loosening due to vibratory loads. Their unique design directs forces away from seams and corners.



Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry

Materials

- ▶ Zinc-Plated Carbon Steel



Original Wej-It Wedge Anchors: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Min. Embed (in.)	Thread Length (in.)	Box Quantity	Carton Quantity
1413	1/4 x 1-3/4	1	1/2	100	600
1423	1/4 x 2-3/4	1	1/2	100	600
1430	1/4 x 3	1	1/2	100	600
5620	5/16 x 2	1-1/4	5/8	100	600
5630	5/16 x 3	1-1/4	5/8	100	600
3820	3/8 x 2	1-1/2	3/4	100	600
3823	3/8 x 2-3/4	1-1/2	3/4	100	600
3832	3/8 x 3-1/2	1-1/2	3/4	50	300
3850	3/8 x 5	1-1/2	3/4	50	300
3860	3/8 x 6	1-1/2	3/4	50	300
1223	1/2 x 2-3/4	2	1	50	300
1232	1/2 x 3-1/2	2	1	50	300
1250	1/2 x 5	2	1	25	150
1260	1/2 x 6	2	1	25	150
1270	1/2 x 7	2	1	25	150
5832	5/8 x 3-1/2	3	1-1/4	25	150
5842	5/8 x 4-1/2	3	1-1/4	25	150
5850	5/8 x 5	3	1-1/4	20	120
5860	5/8 x 6	3	1-1/4	15	90
5870	5/8 x 7	3	1-1/4	15	90
3440	3/4 x 4	3	1-1/2	18	108
3450	3/4 x 5	3	1-1/2	12	72
3460	3/4 x 6	3	1-1/2	12	72
3470	3/4 x 7	3	1-1/2	10	60
3482	3/4 x 8-1/2	3	1-1/2	10	30
3410	3/4 x 10	3	1-1/2	10	30
7880	7/8 x 8	4-1/2	1-3/4	10	30
7810	7/8 x 10	4-1/2	1-3/4	10	30
7812	7/8 x 12	4-1/2	1-3/4	5	15
1080	1 x 8	5-1/2	2	10	30
1010	1 x 10	5-1/2	2	5	15
1012	1 x 12	5-1/2	2	5	15

Sleeve-TITE™ Sleeve Anchors

This anchor is a high-strength pre-assembled expansion anchor designed for anchoring into concrete, masonry, and brick. The Sleeve-TITE anchor has a 6-dimple expansion sleeve over a threaded stud bolt, which provides superior performance in all conditions. These anchors are available in a number of head styles for a wide array of applications.

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Hollow Masonry
- ▶ Solid Masonry

Materials

- ▶ Zinc-Plated Carbon Steel
- ▶ Type 304 Stainless Steel



Acorn Nut: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
ASA1413	1/4 x 1-3/8	1/4	1-1/8	100	1000
ASA1421	1/4 x 2-1/4	1/4	1-1/8	100	800



Hex Nut: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
HSA5612	5/16 x 1-1/2	5/16	1-3/16	100	800
HSA5622	5/16 x 2-1/2	5/16	1-3/16	100	800
HSA3813	3/8 x 1-7/8	3/8	1-1/4	50	400
HSA3830	3/8 x 3	3/8	1-1/4	50	400
HSA3840	3/8 x 4	3/8	1-1/4	50	400
HSA1221	1/2 x 2-1/4	1/2	1-1/2	25	200
HSA1230	1/2 x 3	1/2	1-1/2	25	200
HSA1240	1/2 x 4	1/2	1-1/2	25	200
HSA1260	1/2 x 6	1/2	1-1/2	25	200
HSA5821	5/8 x 2-1/4	5/8	2	25	200
HSA5830	5/8 x 3	5/8	2	25	200
HSA5841	5/8 x 4-1/4	5/8	2	10	80
HSA5860	5/8 x 6	5/8	2	10	80
HSA3422	3/4 x 2-1/2	3/4	2-1/4	10	80
HSA3440	3/4 x 4	3/4	2-1/4	10	80
HSA3461	3/4 x 6-1/4	3/4	2-1/4	10	80

Sleeve-TITE[™] Sleeve Anchors

Rod Coupling: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
CSA3813	3/8 x 1-7/8	3/8	1-1/4	50	400
CSA1221	1/2 x 2-1/4	1/2	1-1/2	25	200
CSA5821*	5/8 x 2-1/4	5/8	2	25	200

* Special Order



Flat Head: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
FSA1421	1/4 x 2-1/4	1/4	1-1/8	100	800
FSA1431	1/4 x 3-1/4	1/4	1-1/8	100	800
FSA1440	1/4 x 4	1/4	1-1/8	100	800
FSA3823	3/8 x 2-3/4	3/8	1-1/4	50	400
FSA3830	3/8 x 3	3/8	1-1/4	50	400
FSA3840	3/8 x 4	3/8	1-1/4	50	400
FSA3850	3/8 x 5	3/8	1-1/4	50	400
FSA3860	3/8 x 6	3/8	1-1/4	50	400



Hex Bolt Head: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
HBSA3813*	3/8 x 1-7/8	3/8	1-1/4	50	400
HBSA3830*	3/8 x 3	3/8	1-1/4	50	400
HBSA3840*	3/8 x 4	3/8	1-1/4	50	400
HBSA1221*	1/2 x 2-1/4	1/2	1-1/2	25	200
HBSA1230*	1/2 x 3	1/2	1-1/2	25	200
HBSA1240*	1/2 x 4	1/2	1-1/2	25	200

* Special Order



Tie-Wire: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
WTS5612	5/16 x 1-1/2	5/16	1-3/16	100	1000

Sleeve-TITE™ Sleeve Anchors



Acorn Nut: Type 304 Stainless Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
ASAX1413	1/4 x 1-3/8	1/4	1-1/8	100	1000
ASAX1421	1/4 x 2-1/4	1/4	1-1/8	100	800



Hex Nut: Type 304 Stainless Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
HSAX5612	5/16 x 1-1/2	5/16	1-3/16	100	800
HSAX5622	5/16 x 2-1/2	5/16	1-3/16	100	800
HSAX3813	3/8 x 1-7/8	3/8	1-1/4	50	400
HSAX3830	3/8 x 3	3/8	1-1/4	50	400
HSAX3840	3/8 x 4	3/8	1-1/4	50	400
HSAX1221	1/2 x 2-1/4	1/2	1-1/2	25	200
HSAX1230	1/2 x 3	1/2	1-1/2	25	200
HSAX1240	1/2 x 4	1/2	1-1/2	25	200
HSAX5841	5/8 x 4-1/4	5/8	2	10	80



Flat Head: Type 304 Stainless Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
FSAX1420	1/4 x 2	1/4	1-1/8	100	800
FSAX1430	1/4 x 3	1/4	1-1/8	100	800
FSAX3830	3/8 x 3	3/8	1-1/4	50	400
FSAX3840	3/8 x 4	3/8	1-1/4	50	400
FSAX3850	3/8 x 5	3/8	1-1/4	50	400
FSAX3860	3/8 x 6	3/8	1-1/4	50	400

POWER-Skru™ Large Diameter Concrete Screws

This anchor is a high-strength screw anchor with self-tapping threads that offer a unique undercutting design for anchoring into concrete and masonry. No secondary setting is needed. The POWER-Skru large diameter concrete screw provides high-strength performance with low installation torque. A heavy duty mechanically galvanized finish is available to enhance corrosion resistance.

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry
- ▶ May Be Suitable For Hollow Masonry

Materials

- ▶ Heat-Treated Carbon Steel

Finish

- ▶ **1/4" Anchors:**
Zinc Electroplated
- ▶ **All Sizes:**
Mechanically Galvanized

**Zinc Electroplated, Heat-Treated Carbon Steel**

Catalog No.	Head Style	Anchor Size (in.)	Drill Bit Dia. (in.)	Baseplate Clearance Hole (in.)	Box Quantity	Carton Quantity
ATEZ1413	Hex	1/4 x 1-3/4	1/4	3/8	100	800
ATEZ1421	Hex	1/4 x 2-1/4	1/4	3/8	100	800
ATEZ1430	Hex	1/4 x 3	1/4	3/8	100	800

COMING SOON!

**Large Diameter Concrete Screws:
Type 316 Stainless Steel**

POWER-Skru™ Large Diameter Concrete Screws**Mechanically Galvanized, Heat-Treated Carbon Steel**

Catalog No.	Head Style	Anchor Size (in.)	Drill Bit Dia. (in.)	Baseplate Clearance Hole (in.)	Box Quantity	Carton Quantity
ATEZG1413	Hex	1/4 x 1-3/4	1/4	3/8	100	800
ATEZG1421	Hex	1/4 x 2-1/4	1/4	3/8	100	800
ATEZG1430	Hex	1/4 x 3	1/4	3/8	100	800
ATEZG3830	Hex	3/8 x 3	3/8	1/2	50	400
ATEZG3840	Hex	3/8 x 4	3/8	1/2	50	400
ATEZG3850	Hex	3/8 x 5	3/8	1/2	25	200
ATEZG3860	Hex	3/8 x 6	3/8	1/2	25	200
ATEZG1230	Hex	1/2 x 3	1/2	5/8	20	160
ATEZG1240	Hex	1/2 x 4	1/2	5/8	20	160
ATEZG1250	Hex	1/2 x 5	1/2	5/8	20	160
ATEZG1260	Hex	1/2 x 6	1/2	5/8	20	160
ATEZG1270	Hex	1/2 x 7	1/2	5/8	20	160
ATEZG5840	Hex	5/8 x 4	5/8	3/4	10	80
ATEZG5850	Hex	5/8 x 5	5/8	3/4	10	80
ATEZG5860	Hex	5/8 x 6	5/8	3/4	10	80
ATEZG5870	Hex	5/8 x 7	5/8	3/4	10	80
ATEZG5880	Hex	5/8 x 8	5/8	3/4	10	40
ATEZG3440	Hex	3/4 x 4	3/4	7/8	10	80
ATEZG3450	Hex	3/4 x 5	3/4	7/8	10	80
ATEZG3460	Hex	3/4 x 6	3/4	7/8	10	60
ATEZG3470	Hex	3/4 x 7	3/4	7/8	5	30

Wej-Con® Concrete Screws

This anchor is a high-strength, case hardened screw with twin-lead, v-notched threads for anchoring into concrete, masonry, and brick. Advanced R-Blocker™ coating offers exceptional test results in salt spray testing. Wej-Con concrete screws install quickly in a pre-drilled hole and can be removed and reinstalled as often as necessary.

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry
- ▶ Hollow Masonry

Materials

- ▶ Heat-treated carbon steel with blue R-Blocker coating
 - 1000+ hours of salt spray resistance per ASTM B117
- ▶ 410 stainless steel with silver R-Blocker coating
 - 1500+ hours of salt spray resistance per ASTM B117 and is also ACQ-compatible.

**Flat Head: Heat-Treated Carbon Steel w/ Blue R-Blocker Coating**

Catalog No.	Anchor Size (in.)	Phillips Drive Size	Box Quantity	Carton Quantity
FCS3611	3/16 x 1-1/4	#2	100	600
FCS3613	3/16 x 1-3/4	#2	100	600
FCS3621	3/16 x 2-1/4	#2	100	600
FCS3623	3/16 x 2-3/4	#2	100	600
FCS3631	3/16 x 3-1/4	#2	100	600
FCS3633	3/16 x 3-3/4	#2	100	600
FCS3640	3/16 x 4	#2	100	600
FCS1411	1/4 x 1-1/4	#3	100	600
FCS1413	1/4 x 1-3/4	#3	100	600
FCS1421	1/4 x 2-1/4	#3	100	600
FCS1423	1/4 x 2-3/4	#3	100	600
FCS1431	1/4 x 3-1/4	#3	100	600
FCS1433	1/4 x 3-3/4	#3	100	600
FCS1440	1/4 x 4	#3	100	600
FCS1450	1/4 x 5	#3	100	600
FCS1460	1/4 x 6	#3	100	600

*One drill bit included per box of screws

Wej-Con® Concrete Screws


**Hex Washer Head: Heat-Treated Carbon Steel
w/ Blue R-Blocker Coating**

Catalog No.	Anchor Size (in.)	Drive Size	Box Quantity	Carton Quantity
HCS3611	3/16 x 1-1/4	5/16" hex with slot	100	600
HCS3613	3/16 x 1-3/4	5/16" hex with slot	100	600
HCS3621	3/16 x 2-1/4	5/16" hex with slot	100	600
HCS3623	3/16 x 2-3/4	5/16" hex with slot	100	600
HCS3631	3/16 x 3-1/4	5/16" hex with slot	100	600
HCS3633	3/16 x 3-3/4	5/16" hex with slot	100	600
HCS3640	3/16 x 4	5/16" hex with slot	100	600
HCS1411	1/4 x 1-1/4	5/16" hex with slot	100	600
HCS1413	1/4 x 1-3/4	5/16" hex with slot	100	600
HCS1421	1/4 x 2-1/4	5/16" hex with slot	100	600
HCS1423	1/4 x 2-3/4	5/16" hex with slot	100	600
HCS1431	1/4 x 3-1/4	5/16" hex with slot	100	600
HCS1433	1/4 x 3-3/4	5/16" hex with slot	100	600
HCS1440	1/4 x 4	5/16" hex with slot	100	600
HCS1450	1/4 x 5	5/16" hex with slot	100	600
HCS1460	1/4 x 6	5/16" hex with slot	100	600

*One drill bit included per box of screws.


Flat Head: 410 Stainless Steel w/ Silver R-Blocker Coating

Catalog No.	Anchor Size (in.)	Phillips Drive Size	Box Quantity	Carton Quantity
FCSS1411	1/4 x 1-1/4	#3	100	600
FCSS1413	1/4 x 1-3/4	#3	100	600
FCSS1421	1/4 x 2-1/4	#3	100	600
FCSS1423	1/4 x 2-3/4	#3	100	600
FCSS1431	1/4 x 3-1/4	#3	100	600
FCSS1433	1/4 x 3-3/4	#3	100	600

*One drill bit included per box of screws.

Wej-Con® Concrete Screws

**Hex Washer Head: 410 Stainless Steel w/ Silver R-Blocker Coating**

Catalog No.	Anchor Size (in.)	Drive Size	Box Quantity	Carton Quantity
HCSS1411	1/4 x 1-1/4	5/16" hex	100	600
HCSS1413	1/4 x 1-3/4	5/16" hex	100	600
HCSS1421	1/4 x 2-1/4	5/16" hex	100	600
HCSS1423	1/4 x 2-3/4	5/16" hex	100	600
HCSS1431	1/4 x 3-1/4	5/16" hex	100	600
HCSS1433	1/4 x 3-3/4	5/16" hex	100	600

*One drill bit included per box of screws

COMING SOON!

**Flat Head Concrete Screws:
304 Stainless Steel**

COMING SOON!

**Hex Washer Head Concrete Screws:
304 Stainless Steel**

Hang-TITE™ Rod Hanger Screws

This anchor is a **one-piece**, internally threaded screw designed for suspending threaded rod vertically overhead for applications like cable-tray, pipe hanging, fire protection, and electrical conduit. It can be installed in a variety of base materials like wood frame columns and beams, steel purlins, bar joists and beams, and concrete ceilings, beams and columns. The Hang-TITE rod hanger screws made for steel and wood applications are also available in a side mount style. Socket driver tools are available for easy installation using a screw gun or hammer drill.

Applications

- ▶ Steel Purlins
- ▶ Wood and Timber
- ▶ Normal Weight Concrete
- ▶ Light Weight Concrete
- ▶ Hollow Core Concrete Plank

Materials

- ▶ Zinc-Plated Carbon Steel



Wood Vertical Hangers: Zinc-Plated Carbon Steel

Catalog No.	Rod Dia. (in.)	Screw Thread Size and Length (in.)	Point Style	Box Quantity	Carton Quantity
HTWV141420	1/4	1/4 x 2	Type 17	100	500
HTWV381410	3/8	1/4 x 1	Type 17	100	500
HTWV381420	3/8	1/4 x 2	Type 17	100	500
HTWV381430	3/8	1/4 x 3	Type 17	100	500
HTWV383822	3/8	3/8 x 2-1/2	Type 17	100	500
HTWV123822	1/2	3/8 x 2-1/2	Type 17	100	500



Wood Side Hangers: Zinc-Plated Carbon Steel

Catalog No.	Rod Dia. (in.)	Screw Thread Size and Length (in.)	Point Style	Box Quantity	Carton Quantity
HTWS381410	3/8	1/4 x 1	Type 17	100	500
HTWS381420	3/8	1/4 x 2	Type 17	100	500
HTWS383822	3/8	3/8 x 2-1/2	Type 17	100	500

Hang-TITE™ Rod Hanger Anchors



Steel Vertical Hangers: Zinc-Plated Carbon Steel

Catalog No.	Rod Dia. (in.)	Screw Thread Size and Length (in.)	Point Style [†]	Box Quantity	Carton Quantity
HTSV141410	1/4	1/4 - 20 x 1	#3	100	500
HTSV381420	3/8	1/4 - 20 x 2	#3	100	500
HTSV381410	3/8	1/4 - 20 x 1 (w/nut)	#3	100	500
HTSV381412	3/8	1/4 - 20 x 1-1/2 (w/nut)	#3	100	500
HTSV381212	3/8	12 - 20 x 1-1/2 (w/nut)	#5	100	500
HTSV121212	1/2	12 - 20 x 1-1/2 (w/nut)	#5	100	500

[†] #3 for Purlins, #5 for Beams



Steel Side Hangers: Zinc-Plated Carbon Steel

Catalog No.	Rod Dia. (in.)	Screw Thread Size and Length (in.)	Point Style [†]	Box Quantity	Carton Quantity
HTSS381410	3/8	1/4 -20 x 1 (w/nut)	#3	100	500
HTSS381412	3/8	1/4 -20 x 1-1/2 (w/nut)	#3	100	500
HTSS381420	3/8	1/4 -20 x 2 (w/nut)	#3	100	500

[†] #3 for Purlins



Concrete Vertical Hangers: Zinc-Plated Carbon Steel

Catalog No.	Rod Dia. (in.)	Screw Thread Size and Length (in.)	Drill Bit Dia. (in.)	Box Quantity	Carton Quantity
HTCV141411	1/4	1/4 x 1-1/4	1/4	100	500
HTCV381412	3/8	1/4 x 1-1/2	1/4	100	500
HTCV123823	1/2	3/8 x 2-3/4	3/8	50	250

Installation Tools

Catalog No.	Description/Size	Box Quantity	Carton Quantity
HTWSST	Universal Steel & Wood Socket	1	10
HTCST14	1/4 Concrete Socket	1	10
HTCST38	3/8 Concrete Socket	1	10
HTCST12	1/2 Concrete Socket	1	10

Ultra-Drop™ Drop-In Anchors

This anchor is an internally threaded, flush mount expansion anchor designed for use in solid concrete, stone, and solid block based materials. The Ultra-Drop drop-in anchor features a knurled body that increases friction between the anchor body and the internal walls of the hole.

Options include: standard, coil thread, lipped and mini. The standard drop-in anchors are also available in 304SS and 316SS.

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry
- ▶ Stone

Internal Thread

- ▶ 1/4" - 3/4" UNC Coarse Thread
- ▶ 1/2" & 3/4" Coil Thread

Notes

- ▶ Setting Tools Sold Separately

Materials

- ▶ Zinc-Plated Carbon Steel
- ▶ Type 304 Stainless Steel
- ▶ Type 316 Stainless Steel



Standard: Zinc-Plated Carbon Steel

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
WD14	3/8	1/4 - 20	1	100	1000
WD38	1/2	3/8 - 16	1-5/8	50	500
WD12	5/8	1/2 - 13	2	50	500
WD58	7/8	5/8 - 11	2-1/2	25	200
WD34	1	3/4 - 10	3-1/4	25	150



Lipped: Zinc-Plated Carbon Steel

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
WDL14	3/8	1/4 - 20	1	100	1000
WDL38	1/2	3/8 - 16	1-5/8	50	500
WDL12	5/8	1/2 - 13	2	50	500



Coil Thread: Zinc-Plated Carbon Steel

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
WDCT12	5/8	1/2 - 6	2	50	500
WDCT34	1	3/4 - 4-1/2	3-1/4	25	150

Ultra-Drop[™] Drop-In Anchors

MINI: Zinc-Plated Carbon Steel

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
WDM14	3/8	1/4 - 20	5/8	100	1000
WDM38	1/2	3/8 - 16	3/4	50	500
WDM12	5/8	1/2 - 13	1	50	400



Standard: Type 304 Stainless Steel

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
WDS14	3/8	1/4 - 20	1	100	1000
WDS38	1/2	3/8 - 16	1-5/8	50	500
WDS12	5/8	1/2 - 13	2	50	500
WDS58	7/8	5/8 - 11	2-1/2	25	200
WDS34	1	3/4 - 10	3-1/4	25	150



Standard: Type 316 Stainless Steel

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
WDSS14	3/8	1/4 - 20	1	100	1000
WDSS38	1/2	3/8 - 16	1-5/8	50	500
WDSS12	5/8	1/2 - 13	2	50	500
WDSS58	7/8	5/8 - 11	2-1/2	25	200
WDSS34	1	3/4 - 10	3-1/4	25	150



Setting Tools

Catalog No.		Sets Anchor Thread Size (in.)	Quantity
ST14	STM14*	1/4	1
ST38	STM38*	3/8	1
ST12	STM12*	1/2	1
ST58	-	5/8	1
ST34	-	3/4	1

* MINI Setting Tool

Hollo Set™ Drop-In Anchors

This anchor is an internally threaded, flush mount expansion anchor designed for use in hollow and solid base materials. In hollow concrete block and precast hollow core plank, the outer wall is generally 1-1/2" thick. When a hole is drilled into the material, there is often spalling on the back side of the wall that can decrease the wall thickness to less than 1" thick. The Hollo Set anchor will still provide high performance in these altered applications, unlike similar products.

Applications

- ▶ Hollow-Core, Precast, and Post-Tension Slabs
- ▶ Solid Base Materials

Internal Thread

- ▶ 1/4" - 1/2" UNC Coarse Thread

Notes

- ▶ Setting Tools Sold Separately

Materials

- ▶ Zamac Alloy Body
- ▶ Zinc-Plated Heat-Treated Carbon Steel Cone



Hollo Set Drop-In Anchors

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
WDHS14	3/8	1/4 - 20	7/8	100	1000
WDHS38	5/8	3/8 - 16	1-5/16	50	500
WDHS12	3/4	1/2 - 13	1-3/4	50	500



Setting Tools: Solid Base Materials

Catalog No.	Sets Anchor Thread Size (in.)	Quantity
STH14	1/4	1
STH38	3/8	1
STH12	1/2	1



Setting Tools: Hollow Base Materials

Catalog No.	Sets Anchor Thread Size (in.)	Quantity
STSH14	1/4	1
STSH38	3/8	1
STSH12	1/2	1

POWER-Drop™ Drop-In Anchors

This anchor provides wedge anchor performance with the convenience of a drop-in. The safety shoulder supports the clip when the anchor is under strain to eliminate bolt-end collapse and/or clip slippage under ultimate loading conditions. These seismic rated drop-in anchors may be used with machine screws, tamper-proof bolts, threaded rod and other male-threaded fasteners 3/8" – 1" in diameter. **Drill bit diameter equals the anchor diameter.**

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry

Internal Thread

- ▶ 3/8" – 1" UNC coarse thread

Materials

- ▶ Zinc-Plated Carbon Steel

**POWER-Drop Anchors: Zinc-Plated Carbon Steel**

Catalog No.	Thread Size (UNC)	Anchor Size (in.)	Min. Hole Depth (in.)	Box Quantity	Carton Quantity
PD38	3/8 - 16	1/2 x 2-5/16	3	25	200
PD12	1/2 - 13	5/8 x 3-3/32	4	10	80
PD58	5/8 - 11	7/8 x 3-13/16	5	5	30
PD34	3/4 - 10	1 x 4-5/8	5-3/4	5	30
PD1	1 - 8	1-1/4 x 5	6-1/2	5	30

***Note: One setting tool included per box of anchors**

Expansion Shields

Single Expansion Shields are a corrosion resistant anchor that is designed to be used with a machine bolt in concrete, brick, block, and stone. The anchor comes pre-assembled and consists of a zamac alloy anchor body and an expansion cone. The expansion cone is drawn into the anchor body as the machine bolt is tightened into the anchor. The anchor will retain its holding power even if the mating bolt is removed and replaced.

Applications

- ▶ Normal Weight Concrete
- ▶ May Be Suitable for Lightweight Concrete

Materials

- ▶ Zamac Alloy



Single Expansion Shields: Zamac Alloy

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
SES14	1/2	1/4 - 20	1-5/16	100	1000
SES56	5/8	5/16 - 18	1-1/2	50	500
SES38	5/8	3/8 - 16	1-1/2	50	500
SES12	7/8	1/2 - 13	2	25	200
SE558	1	5/8 - 11	2-5/8	25	200

Double Expansion Shields are a corrosion resistant anchor that is designed to be used with a machine bolt in concrete, brick, block, and stone. The anchor comes pre-assembled and consists of a zamac alloy anchor body, two expansion cones (one at each end of the anchor), and a wire expanding ring that holds the entire anchor together. The expansion cones are drawn in at each end of the anchor as the machine bolt is tightened into the anchor – ensuring consistent and even expansion along the entire anchor body. Recommended for anchoring into base materials of questionable strength.

Applications

- ▶ Normal Weight Concrete
- ▶ May Be Suitable for Lightweight Concrete

Materials

- ▶ Zamac Alloy



Double Expansion Shields: Zamac Alloy

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
DES14	1/2	1/4 - 20	1-3/8	100	1000
DES56	5/8	5/16 - 18	1-5/8	50	500
DES38	3/4	3/8 - 16	2	50	400
DES12	7/8	1/2 - 13	2-1/2	25	200
DES58	1	5/8 - 11	2-3/4	25	200

Lag Screw Shields

This anchor is a corrosion resistant anchor designed to be used with lag screws in concrete and the mortar joints of brick and block walls. For soft or weak masonry, the long version is recommended to add strength to the substrate. The short version is recommended for harder masonry materials to reduce drilling time.

Applications

- ▶ Normal Weight Concrete
- ▶ Solid Masonry
- ▶ May Be Suitable for Lightweight Concrete and Hollow Masonry

Materials

- ▶ Zamac Alloy



Short Lag Screw Shields: Zamac Alloy

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
LSS14	1/2	1/4 - 10	1	50	1000
LSS56	1/2	5/16 - 9	1-1/4	50	1000
LSS38	5/8	3/8 - 7	1-3/4	50	500
LSS12	3/4	1/2 - 6	2	25	250
LSS58	7/8	5/8 - 5	2	25	250



Long Lag Screw Shields: Zamac Alloy

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
LSL14	1/2	1/4 - 10	1-1/2	50	1000
LSL56	1/2	5/16 - 9	1-3/4	50	1000
LSL38	5/8	3/8 - 7	2-1/2	50	400
LSL12	3/4	1/2 - 6	3	25	250
LSL58	7/8	5/8 - 5	3-1/2	25	250

Machine Screw Shields

This anchor is a corrosion resistant anchor designed to be used with a machine bolt in concrete, block, brick or stone. This two-piece anchor is made of a zamac alloy sleeve and an internally threaded cone.

Applications

- ▶ Normal Weight Concrete
- ▶ Solid Masonry
- ▶ May Be Suitable for Lightweight Concrete and Hollow Masonry

Materials

- ▶ Zamac Alloy



Machine Screw Shields: Zamac Alloy

Catalog No.	Drill Bit Dia. (in.)	Thread Size (UNC)	Anchor Length (in.)	Box Quantity	Carton Quantity
MS14	1/2	1/4 - 20	7/8	100	2000
MS56	5/8	5/16 - 18	1	50	1000
MS38	3/4	3/8 - 16	1-1/4	50	500
MS12	7/8	1/2 - 13	1-1/2	25	250

Strike-It™ Center Pin Drive Anchors

This anchor is an impact expansion anchor designed for medium and heavy duty anchoring into concrete and grout-filled block. With its unique all-in-one serrated nut and washer, it offers superior holding and vibration resistance.

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry

Materials

- ▶ Hot Rolled Steel Anchor Body with a Hot Wrought Iron Pin
- ▶ Yellow Zinc Dichromate Coating Over All


**Center Pin Drive Anchors:
Yellow Zinc Dichromate Coated Carbon Steel**

Catalog No.	Anchor Size (in.)	Thread Length (in.)	Drill Bit Dia. (in.)	Box Quantity	Carton Quantity
CP1413	1/4 x 1-3/4	5/8	1/4	100	800
CP1423	1/4 x 2-3/8	3/4	1/4	100	800
CP5620	5/16 x 2	1/2	5/16	100	800
CP5623	5/16 x 2-3/4	1-1/8	5/16	100	800
CP3823	3/8 x 2-3/8	7/8	3/8	50	400
CP3832	3/8 x 3-1/2	1-1/8	3/8	50	400
CP3843	3/8 x 4-3/4	1-1/8	3/8	50	400
CP1223	1/2 x 2-3/4	7/8	1/2	25	200
CP1232	1/2 x 3-1/2	1	1/2	25	200
CP1243	1/2 x 4-3/4	1-3/4	1/2	25	200
CP1260	1/2 x 6	1-7/8	1/2	25	200
CP5840	5/8 x 4	1-1/4	5/8	10	80
CP5860	5/8 x 6	1-1/4	5/8	10	80
CP3450	3/4 x 5	1-3/4	3/4	10	30
CP3460	3/4 x 6	1-3/4	3/4	10	30
CP3472	3/4 x 7 1/2	2	3/4	10	30

Nail-It™ Drive Nail Anchors

This anchor is a two-piece nail-in anchor comprised of a corrosion resistant zamac anchor body and a steel or stainless steel drive nail. The Nail-It anchor is easy to install and ideal for light-duty and tamper-proof applications in concrete, block, brick or stone.

Applications	Materials
▶ Normal Weight Concrete ▶ Solid Masonry ▶ May Also Be Suitable for Lightweight Concrete and Hollow Masonry ▶ Not Recommended for Overhead Applications.	▶ Die Cast Zamac Alloy Anchor Body with a Zinc-Plated Cold Rolled Steel Pin ▶ Zamac Alloy Anchor Body with an Unplated Stainless Steel Pin



Drive Nail Anchors: Zamac Alloy Body with Steel Pin

Catalog No.	Anchor Size (in.)	Box Quantity	Carton Quantity
DN3678	3/16 x 7/8	100	1000
DN1403	1/4 x 3/4	100	1000
DN1410	1/4 x 1	100	1000
DN1411	1/4 x 1-1/4	100	1000
DN1412	1/4 x 1-1/2	100	800
DN1420	1/4 x 2	100	800
DN1422	1/4 x 2-1/2	100	800
DN1430	1/4 x 3	100	800
DN1440	1/4 x 4	100	800



Drive Nail Anchors: Zamac Alloy Body with Stainless Steel Pin

Catalog No.	Anchor Size (in.)	Box Quantity	Carton Quantity
DNS1410	1/4 x 1	100	1000
DNS1411	1/4 x 1-1/4	100	1000
DNS1412	1/4 x 1-1/2	100	800
DNS1420	1/4 x 2	100	800

Screw-In™ Drive Screw Anchors

This anchor is a two-piece drive screw anchor comprised of a corrosion resistant zamac anchor body and a **removable** steel Phillips screw. The #2 Phillips screw can be easily removed after the anchor is properly set. The Screw-In anchor is ideal for light-duty applications in concrete, block, brick or stone.

Applications

- ▶ Normal Weight Concrete
- ▶ Solid Masonry
- ▶ May Also Be Suitable for Lightweight Concrete and Hollow Masonry

Materials

- ▶ Die Cast Zamac Alloy Anchor Body with a Zinc-Plated Steel Screw



Drive Screw Anchors: Zamac Allow Body with Steel Screw

Catalog No.	Anchor Size (in.)	Screw Style	Box Quantity	Carton Quantity
DNHS1403	1/4 x 3/4	#2 Phillips	100	1000
DNHS1410	1/4 x 1	#2 Phillips	100	1000
DNHS1411	1/4 x 1-1/4	#2 Phillips	100	1000
DNHS1412	1/4 x 1-1/2	#2 Phillips	100	800
DNHS1420	1/4 x 2	#2 Phillips	100	800
DNHS1422*	1/4 x 2-1/2	#2 Phillips	100	800
DNHS1430*	1/4 x 3	#2 Phillips	100	800

* Special Order

Slam-It™ Split Drive Anchors

This anchor is a one-piece, pre-formed tamper-proof anchor that is ideal for anchoring into solid concrete and stone. The Slam-It anchor is easy to install and is available in a flat head or a mushroom head.

Applications

- ▶ Normal Weight Concrete
- ▶ Stone

Materials

- ▶ Zinc-Plated Carbon Steel



Flat Head Split-Drive Anchors: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Box Quantity	Carton Quantity
SDF1412	1/4 x 1-1/2	100	800
SDF1420	1/4 x 2	100	800
SDF1422	1/4 x 2-1/2	100	800
SDF1430	1/4 x 3	100	800
SDF1432	1/4 x 3-1/2	100	800
SDF1440	1/4 x 4	100	800



Mushroom Head Split-Drive Anchors: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Box Quantity	Carton Quantity
SDR1412	1/4 x 1-1/2	100	800
SDR1420	1/4 x 2	100	800
SDR1422	1/4 x 2-1/2	100	800
SDR1430	1/4 x 3	100	800

Pound-It™ Drive Anchors

This anchor is a tamper-proof and vibration resistant one-piece anchor designed for use in concrete, grout-filled block, or masonry. The Pound-It Drive Anchor is pre-formed with a bend along the anchor shaft that creates an expansion wedge that locks the anchor in place. There is no need for secondary tightening, which speeds up and greatly reduces the cost of the anchor installation.

Applications

- ▶ Normal Weight Concrete
- ▶ Light Weight Concrete
- ▶ Grouted Concrete Masonry
- ▶ Stone

Materials

- ▶ Zinc-Plated Carbon Steel
- ▶ Type 316 Stainless Steel

**Flat-Head Drive Anchors: Zinc-Plated Carbon Steel**

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
PFH1420	1/4 x 2	1/4	1-1/4	100	1000
PFH1422	1/4 x 2-1/2	1/4	1-1/4	100	1000
PFH1430	1/4 x 3	1/4	1-1/4	100	1000
PFH1432	1/4 x 3-1/2	1/4	1-1/4	100	1000
PFH1440	1/4 x 4	1/4	1-1/4	100	1000

**Forming Head Drive Anchors: Zinc-Plated Carbon Steel**

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
PFS3623	3/16 x 2-3/4	3/16	1-1/4	100	1000
PFS1423	1/4 x 2-3/4	1/4	1-1/4	100	1000

**Tie-Wire Drive Anchors: Zinc-Plated Carbon Steel**

Catalog No.	Anchor Size (in.)	Tie Wire Hole (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
PTW3611	3/16 x 1-1/4	3/16	3/16	1-1/8	100	1000
PTW1413	1/4 x 1-3/4	9/32	1/4	1-1/8	100	1000

**Rod-Coupling Drive Anchors: Zinc-Plated Carbon Steel**

Catalog No.	Anchor Size (in.)	Thread Size (UNC)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
PPS14	1/4 x 1-7/8	1/4 - 20	3/16	1-1/4	100	1000
PPS38	3/8 x 2-3/8	3/8 - 16	1/4	1-3/4	50	500

Pound-It™ Drive Anchors



Mushroom Head Drive Anchors: Zinc-Plated Carbon Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
PMH3610	3/16 x 1	3/16	7/8	100	1000
PMH3611	3/16 x 1-1/4	3/16	7/8	100	1000
PMH3612	3/16 x 1-1/2	3/16	1-1/4	100	1000
PMH3620	3/16 x 2	3/16	1-1/4	100	1000
PMH3622	3/16 x 2-1/2	3/16	1-1/4	100	1000
PMH3630	3/16 x 3	3/16	1-1/4	100	1000
PMH3632	3/16 x 3-1/2	3/16	1-1/4	100	1000
PMH3640	3/16 x 4	3/16	1-1/4	100	1000
PMH1410	1/4 x 1	1/4	7/8	100	1000
PMH1411	1/4 x 1-1/4	1/4	1	100	1000
PMH1412	1/4 x 1-1/2	1/4	1-1/4	100	1000
PMH1420	1/4 x 2	1/4	1-1/4	100	1000
PMH1422	1/4 x 2-1/2	1/4	1-1/4	100	1000
PMH1430	1/4 x 3	1/4	1-1/4	100	1000
PMH1432	1/4 x 3-1/2	1/4	1-1/4	100	1000
PMH1440	1/4 x 4	1/4	1-1/4	100	1000
PMH3820	3/8 x 2	3/8	1-3/4	25	250
PMH3822	3/8 x 2-1/2	3/8	1-3/4	25	250
PMH3830	3/8 x 3	3/8	1-3/4	25	250
PMH3832	3/8 x 3-1/2	3/8	1-3/4	25	250
PMH3840	3/8 x 4	3/8	1-3/4	25	250
PMH3850	3/8 x 5	3/8	1-3/4	25	250
PMH3860	3/8 x 6	3/8	1-3/4	25	250



Mushroom Head Drive Anchors: Type 316 Stainless Steel

Catalog No.	Anchor Size (in.)	Drill Bit Dia. (in.)	Min. Embed. (in.)	Box Quantity	Carton Quantity
PMHSS3610	3/16 x 1	3/16	7/8	100	1000
PMHSS3611	3/16 x 1-1/4	3/16	7/8	100	1000
PMHSS3612	3/16 x 1-1/2	3/16	1-1/4	100	1000
PMHSS3620	3/16 x 2	3/16	1-1/4	100	1000
PMHSS1411	1/4 x 1-1/4	1/4	1	100	1000
PMHSS1412	1/4 x 1-1/2	1/4	1-1/4	100	1000
PMHSS1420	1/4 x 2	1/4	1-1/4	100	1000
PMHSS1422	1/4 x 2-1/2	1/4	1-1/4	100	1000
PMHSS1430	1/4 x 3	1/4	1-1/4	100	1000
PMHSS3820	3/8 x 2	3/8	1-3/4	25	250
PMHSS3822	3/8 x 2-1/2	3/8	1-3/4	25	250
PMHSS3830	3/8 x 3	3/8	1-3/4	25	250

SNAPTOGGLE[®] Heavy-Duty Toggle Bolts

SNAPTOGGLE heavy-duty toggle bolts carry twice the load in a smaller hole than standard wing anchors. A new, patented strap design with sturdier straps and smaller ratchet interval adjusts more precisely and snaps off flush to the surface. SNAPTOGGLE heavy-duty toggle bolts do NOT spin when installed with a screw gun and provide superior holding with metal-to-metal fastening.



MADE IN THE USA

**Applications**

- ▶ Wallboard/Drywall
- ▶ Hollow Masonry

Channel Thread

- ▶ UNC or Metric Machine Screw Thread

Grip Range

- ▶ BA, BB, BM5, BM6:
3/8" – 3-5/8"
- ▶ BE, BC, BD, BM8, BM10:
3/8" – 2-1/2"
- ▶ BAL, BBL, BM5L, BM6L:
2" – 9-1/2"

Materials

- ▶ Metal channel:
trivalent zinc-plated
cold rolled steel or 304
stainless steel
- ▶ Straps and handle:
polystyrene
- ▶ Cap: polypropylene

**SNAPTOGGLE Toggle Bolts
with Zinc-Plated Carbon Steel Channels****

Catalog No.	Style	Drill Dia. (in.)	Thread Size	Bolts Included	Box/ Bag (pcs.)	Master Carton (pcs.)
24013	BA	1/2	3/16-24	–	100	1000
25013	BA	1/2	3/16-24	–	50	500
50375	BA	1/2	3/16-24	yes	10	120
50350	BA	1/2	3/16-24	yes	2	200
24014	BB	1/2	1/4-20	–	100	1000
25014	BB	1/2	1/4-20	–	50	500
50425	BB	1/2	1/4-20	yes	10	120
50400	BB	1/2	1/4-20	yes	2	200
21017	BE	3/4	5/16-18	–	25	250
21015	BC	3/4	3/8-16	–	25	250
21016	BD	3/4	1/2-13	–	25	250
25029	BM5 Metric	1/2	M5 (5 mm)	–	50	500
25024	BM6 Metric	1/2	M6 (6 mm)	–	50	500
21031	BM8 Metric	3/4	M8 (8 mm)	–	25	250

continues on page 35

SNAPTOGGLE[®] Heavy-Duty Toggle BoltsSNAPTOGGLE Toggle Bolts
with Zinc-Plated Carbon Steel Channels***continued from page 34*

Catalog No.	Style	Drill Dia. (in.)	Thread Size	Bolts Included	Box/ Bag (pcs.)	Master Carton (pcs.)
21035	BM10 Metric	3/4	M10 (10 mm)	–	25	250
21049	BAL Long	1/2	3/16-24	–	50	500
21050	BBL Long	1/2	1/4-20	–	50	500
21064	BM5L Metric Long	1/2	M5 (5 mm)	–	50	500
21025	BM6L Metric Long	1/2	M6 (6 mm)	–	50	500

** All bags and boxes must be purchased in master carton quantities, except for stainless steel boxes, long toggle bolts and metric sizes.

SNAPTOGGLE Toggle Bolts with Stainless Steel[†] Channels**

Catalog No.	Style	Drill Dia. (in.)	Thread Size	Bolts Included	Box/ Bag (pcs.)	Master Carton (pcs.)
24020	BAS	1/2	3/16-24	–	100	1000
25020	BAS	1/2	3/16-24	–	50	500
50435	BAS	1/2	3/16-24	yes	2	200
24021	BBS	1/2	1/4-20	–	100	1000
25021	BBS	1/2	1/4-20	–	50	500
50440	BBS	1/2	1/4-20	yes	2	200
21022	BCS	3/4	3/8-16	–	25	250
21023	BDS	3/4	1/2-13	–	25	250
25030	BM5S Metric	1/2	M5 (5 mm)	–	50	500
25026	BM6S Metric	1/2	M6 (6 mm)	–	50	500
21032	BM8S Metric	3/4	M8 (8 mm)	–	25	250
21036	BM10S Metric	3/4	M10 (10 mm)	–	25	250
21059	BALS Long	1/2	3/16-24	–	50	500
21060	BBLS Long	1/2	1/4-20	–	50	500
21065	BM5LS Metric Long	1/2	M5 (5 mm)	–	50	500
21061	BM6LS Metric Long	1/2	M6 (6 mm)	–	50	500

** All bags and boxes must be purchased in master carton quantities, except for stainless steel boxes, long toggle bolts and metric sizes.

[†] SNAPTOGGLE bolts with stainless steel channels offer the same grip range as their carbon steel equivalents.

SnapSku® Self-Drilling Drywall Anchors

SnapSku anchors feature a built-in "positive-stop" that prevents over-driving the anchor when using a screw gun or hand drill. They activate and lock with an audible "POP", providing positive feedback that they are installed correctly. No pre-drilled hole is required, and a unique tip prevents "walking" to ensure accurate and easy installation. They do not back out of the wall when the screw is removed and can be removed easily, without damaging the wall.



Applications

- ▶ 3/8" – 5/8" wallboard/drywall

Materials

- ▶ Injection-molded, glass-filled nylon (proprietary thermoplastic alloy)

Minimum Screw Length

- ▶ 1-1/4" + thickness of item being anchored



Regular SP anchors accept screw diameter sizes #6, #7, **#8 (preferred)**, #10

SnapSku Standard Anchors

Catalog No.	Included Screw Size In Bag/Box	Box/Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
30010	100 #8 x 1-1/2 Combo Screws	100	1000	3000
30011	No Screws	100	1000	3000
30012	50 #8 x 1-1/2" Combo Screws	50	500	2500
50125	20 #8 x 1-1/2" Combo Screws	20	200	2000
50100	4 #8 x 1-1/2" Combo Screws	4	40	800



MINI SPM anchors accept screw diameter sizes **#6 (preferred)**, #7, #8

SnapSku MINI Anchors

Catalog No.	Included Screw Size In Bag/Box	Box/Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
30030	100 #6 x 1-1/4 Combo Screws	100	1000	5000
30031	No Screws	100	1000	5000
30032	50 #6 x 1-1/4 Combo Screws	50	500	2500
50175	25 #6 x 1-1/4 Combo Screws	25	250	2500
50150	6 #6 x 1-1/4 Combo Screws	6	60	1200

ALLIGATOR[®] All-Purpose Anchors

ALLIGATOR anchors are the most **versatile** anchors that work in almost all building materials. When installed in hollow material, the screw engages the ALLIGATOR anchor's teeth, causing the anchor to expand, pop open and lock on the wall. In solid materials, the ALLIGATOR anchor expands up to twice its original length, filling in all the gaps and spaces - like an adhesive. ALLIGATOR anchors also feature fins that prevent spinning and countersink, even when using a screw gun. Two styles are available: flanged for use where a cavity is anticipated (drywall, hollow brick, etc.) and unflanged for push-through mounting.

**Applications**

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry
- ▶ Hollow Masonry
- ▶ Wallboard/Drywall

Materials

- ▶ Specially formulated, inert grade of self-lubricating, translucent, non-corrodible polypropylene

Drill Dia. = Anchor Dia.

- ▶ AF5 / A5 = 3/16"
- ▶ AF6 / A6 = 1/4"
- ▶ AF8 / A8 = 5/16"
- ▶ A10 = 3/8"

**ALLIGATOR Anchors: With Flange**

Catalog No.	Style	Min. Wall Thick.	Screw Size Range	Included Screw Size*	Box/ Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
13103	AF5	1/4"	#4 – 3/16" SMS	No Screw	200	2000	10000
50445	AF5	1/4"	#4 – 3/16" SMS	#8 x 1-1/4	6	60	1200
50450	AF5	1/4"	#4 – 3/16" SMS	#8 x 1-1/4	20	200	2000
13101	AF6	3/8"	#6 – 1/4" lag	No Screw	100	1000	5000
50470	AF6	3/8"	#6 – 1/4" lag	#10 x 1-1/2	6	60	1200
50475	AF6	3/8"	#6 – 1/4" lag	#10 x 1-1/2	20	200	2000
13102	AF8	1/2"	#8 – 5/16" lag	No Screw	100	1000	5000
50490	AF8	1/2"	#8 – 5/16" lag	#12 x 1-3/4	6	60	1200
50500	AF8	1/2"	#8 – 5/16" lag	#12 x 1-3/4	20	200	2000

* In bags only. SMS: Sheet Metal Screw

ALLIGATOR® All-Purpose Anchors



ALLIGATOR Anchors: No Flange

Catalog No.	Style	Screw Size Range	Included Screw Size*	Box/ Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
13106	A5	#4 – 3/16" SMS	No Screw	200	2000	10000
13104	A6	#6 – 1/4" lag	No Screw	100	1000	5000
50460	A6	#6 – 1/4" lag	#10 x 1-1/2	6	60	1200
13105	A8	#8 – 5/16" lag	No Screw	100	1000	5000
13107	A10	#10 – 3/8" lag	No Screw	50	500	2500
50510	A10	#10 – 3/8" lag	#14 x 2-1/4	4	40	800

* In bags only. SMS: Sheet Metal Screw



TOGGLER[®] Plastic Toggle Anchors

TOGGLER plastic toggle anchors provide a secure, vibration-proof anchoring for medium loads. The third-generation design offers a key-activated positive locking system that provides increased holding strength and abuse resistance. They are vibration and shock proof, and won't damage walls or ceilings.



Six styles, designed for specific grip ranges, are available. All install in only a small 5/16" hole and can be pre-installed without the screw. Anti-rotation fins prevent spinning, even when using a screw gun. All TOGGLER plastic toggle anchors will function without modification as wedge or as expansion anchors in materials thicker than the anchor's grip range. They are all non-conductive (Dielectric constant 2.30 x 106Hz) and non-corrodible.

Applications

- ▶ Wallboard/drywall, including anchoring of electrical apparatus and in environments that are corrosive or have temperature ranging from -20° F to 212° F

Materials

- ▶ Specially formulated grade of non-corrodible polypropylene

Drill Bit Diameter

- ▶ 5/16" for all sizes



TA Hollow-Core Door/Thin Panel Anchors are designed for material thicknesses of 1/8" - 1/4" and accept screw diameters #8 – #12.

TA[®] Hollow Core Door/Thin Panel Anchors

Catalog No.	Included Screw Size*	Box / Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11009	no screws	100	1000	5000
50275	#8 x 1-1/4	5	50	1000

* In bags only. SMS: Sheet Metal Screw



TB Residential Drywall Anchors are for wall thicknesses 3/8" - 1/2" and accept screw diameters #6 – #14.

TB[®] Residential Drywall Anchors

Catalog No.	Included Screw Size*	Box / Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11010	no screws	100	1000	5000
50300	#8 x 1-1/2	5	50	1000
50525	#8 x 1-1/2	20	200	2000

* In bags only. SMS: Sheet Metal Screw

TOGGLER® Plastic Toggle Anchors



TC Commercial Drywall Anchors are for wall thicknesses of 5/8" - 3/4" and accept screw diameters #6 – #14.

TC® Commercial Drywall Anchors

Catalog No.	Included Screw Size*	Box / Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11011	no screws	100	1000	5000
50325	#8 x 1-3/4	5	50	1000
50550	#8 x 1-3/4	20	200	2000

* In bags only. SMS: Sheet Metal Screw



TD Double Drywall Anchors are for wall thicknesses of 1" and accept screw diameters #6 – #14.

TD™ Double Drywall Anchors

Catalog No.	Included Screw Size	Box Quantity (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11021	no screws	50	500	2500



T35 Hollow Wall Anchors are for wall thicknesses of 1-3/8" and **T39** are for 1-1/2". Both accept screw diameters #6 – #14.

T35™ and T39™ Hollow Wall Anchors

Catalog No.	Anchor	Included Screw Size	Box Quantity (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11029	T35	no screws	50	500	2500
11030	T39	no screws	25	250	1250



TOGGLER[®] Specialty AnchorsTOGGLER[®] TH[®] Picture Hook Anchors

TH anchors allow you to hang paintings, prints, mirrors, etc. quickly, easily and securely. They feature a specially-designed, built-in hook that holds the weight of the application on the screw, not below it, providing maximum holding and preventing pull-out.

**Applications**

- ▶ Attaching wall hangings to wallboard/drywall 3/8" – 1/2"
- ▶ Also works in concrete or masonry

Materials

- ▶ Specially formulated grade of non-corrodible polypropylene

Recommended Screw Size

- ▶ #6 – #14 x 1-1/2"

TH Picture Hook Anchors

Catalog No.	Included Screw Size*	Box / Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11012	no screws	100	1000	5000
50225	#8 x 1-1/2	5	50	1000

* In bags only. SMS: Sheet Metal Screw

TBS1 Shelving Anchors



TBS1 anchors feature a built-in spacer that prevents the anchor from being jacked out of the wall during installation. They can be used on warm or wet walls when ventilation is needed behind the installed object.

**Applications**

- ▶ Attaching standard and bracket shelving to 3/8" – 1/2" wallboard/drywall.
- ▶ Also for attaching objects when ventilation is needed between the object and the wall
- ▶ Also works in concrete or masonry

Materials

- ▶ Specially formulated grade of non-corrodible polypropylene

Recommended Screw Size

- ▶ #7 x 1-3/4" flat head

TBS1 Shelving Anchors

Catalog No.	Included Screw Size	Box Quantity (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11023	no screws	50	500	2500

TOGGLER® Specialty Anchors

TBS2 Pegboard Anchors



TBS2 anchors feature a built-in spacer that holds the pegboard the proper distance from the wall to allow peg hooks to work, allowing full use of the pegboard space. They eliminate the need for furring strips, saving time and money.



Applications

- ▶ Attaching pegboards to wallboard/drywall 3/8" – 1/2"
- ▶ Also works in concrete or masonry

Materials

- ▶ Specially formulated grade of non-corrodible polypropylene

Recommended Screw Size

- ▶ #8 x 1-3/4"

TBS2 Pegboard Anchors

Catalog No.	Included Screw Size*	Box / Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11022	no screws	50	500	2500
50200	#8 x 1-3/4	9	90	1800

* In bags only. SMS: Sheet Metal Screw

TBW Wire Shelf Anchors



TBW anchors include a locking retainer clip so shelves don't tip, even with uneven loads. They are ideal for use with wire shelving systems like ClosetMaid® and are perfect for closet systems and kitchen, garage or workshop shelves.



Applications

- ▶ Attaching wire shelving systems to wallboard/drywall 3/8" – 1/2"
- ▶ Also works in concrete or masonry

Materials

- ▶ Specially formulated grade of non-corrodible polypropylene

Recommended Screw Size

- ▶ #8 x 1-3/4"

TBW Wire Shelf Anchors

Catalog No.	Included Screw Size*	Box / Bag (pcs.)	Inner Carton (pcs.)	Master Carton (pcs.)
11024	no screws	50	500	2500
50250	#8 screws	5	50	1000

* In bags only. SMS: Sheet Metal Screw

TOGGLER[®] Combo Kits

TOGGLER Combo Kits provide a variety of anchors in one simple package. The reusable plastic box is a great starter kit for home or office. **Kits include screws** needed for each anchor style.



TOGGLER 44 Piece High-Performance Combo Kit

- ▶ 10 SP[®] SnapSku[®] Self-Drilling Drywall Anchors
- ▶ 10 SPM SnapSku MINI Self-Drilling Drywall Anchors
- ▶ 10 TB[®] (3/8"-1/2") Plastic Toggle Anchors
- ▶ 4 BA (3/16") SNAPTOGGLE[®] Heavy-Duty Toggle Bolts
- ▶ 10 AF6 (1/4") ALLIGATOR[®] Anchors



TOGGLER 50 Piece SnapSku Kit

- ▶ 25 SP SnapSku Self-Drilling Drywall Anchors
- ▶ 25 SPM SnapSku MINI Self-Drilling Drywall Anchors

TOGGLER[®] Combo Kits

Catalog No.	Description	Carton Quantity
33350	High-Performance Combo Kit. 44 Anchors & 44 Screws	6
57125	SnapSku Kit. 50 anchors & 50 Screws	12

Standard Wing Toggles

This is a two-part anchor consisting of a machine bolt and a spring wing toggle. Its snap-open action eases installation and spreads the working load over a greater surface area. It is designed for use in wallboard/drywall, block and other hollow base materials.

Applications

- ▶ Wallboard/Drywall
- ▶ Hollow Masonry

Materials

- ▶ Zinc-plated carbon steel

Mating Bolt Head Style

- ▶ Mushroom Combo Head



Wing Toggles: Zinc-Plated Carbon Steel

Catalog No.	Bolt Size (in.)	Drill Dia. (in.)	Thread Size UNC	Box Quantity	Carton Quantity
TBM1830	1/8 x 3	1/2	6-32	50	500
TBM1840	1/8 x 4	1/2	6-32	50	500
TBM3630	3/16 x 3	9/16	10-24	50	500
TBM3640	3/16 x 4	9/16	10-24	50	500
TBM3650	3/16 x 5	9/16	10-24	50	500
TBM3660	3/16 x 6	9/16	10-24	50	400
TBM1430	1/4 x 3	11/16	1/4-20	50	400
TBM1440	1/4 x 4	11/16	1/4-20	50	400
TBM1450	1/4 x 5	11/16	1/4-20	50	400
TBM1460	1/4 x 6	11/16	1/4-20	50	400
TBM3830	3/8 x 3	1	3/8-16	25	200
TBM3840	3/8 x 4	1	3/8-16	25	200
TBM3850	3/8 x 5	1	3/8-16	25	200
TBM3860	3/8 x 6	1	3/8-16	25	200

Hollow Wall Anchors

These sleeve type anchors provide greater holding power than nails or screws in hollow walls. Fixtures can be removed or replaced without removing the anchor. They are available in two versions: standard and drive. Hollow wall drive anchors allow fast installation, since no pre-drilling is required.

Applications

- ▶ Wallboard/Drywall
- ▶ Plaster
- ▶ Plywood
- ▶ Hollow Masonry

Materials

- ▶ Zinc-plated carbon steel



Hollow Wall Anchors: Zinc-Plated Carbon Steel

Catalog No.	Style	Anchor Dia. (in.)	Drill Dia. (in.)	Wall Thickness (in.)	Box Quantity	Carton Quantity
HWXS18	Extra Short	1/8	5/16	1/8 – 1/4	100	2000
HWS18	Short	1/8	5/16	1/8 – 1/2	100	2000
HWS36	Short	3/16	3/8	1/8 – 5/8	50	1000
HWS14	Short	1/4	7/16	1/8 – 5/8	50	500
HWL18	Long	1/8	5/16	5/8 – 7/8	100	1000
HWL36	Long	3/16	3/8	5/8 – 1-1/4	50	500
HWL14	Long	1/4	7/16	5/8 – 1-1/4	50	500



Hollow Wall Drive Anchors: Zinc-Plated Carbon Steel

Catalog No.	Style	Anchor Dia. (in.)	Drill Dia. (in.)	Wall Thickness (in.)	Box Quantity	Carton Quantity
HWSD18	Short Drive	1/8	5/16	1/8 – 1/2	100	1000
HWLD18	Long Drive	1/8	5/16	5/8 – 3/4	100	1000

Self-Drilling Drywall Anchors

These one-piece light-duty anchors are designed for fast installation into wallboard/drywall. They are available in both nylon and zamac alloy.

Applications	Materials
▶ 3/8" – 1" Wallboard/Drywall	▶ Injection-molded nylon or zamac alloy
	Mating Screw Size
	▶ #6 or #8



Nylon				
Catalog No.	Wall Thickness	Mating Screw Size	Box Quantity	Carton Quantity
DWAN6	3/8" - 5/8"	#6	100	1000
DWAN8	3/8" – 1"	#8	100	1000



Zinc-Coated Zamac Alloy				
Catalog No.	Wall Thickness	Mating Screw Size	Box Quantity	Carton Quantity
DWAS6	3/8" - 5/8"	#6	100	1000
DWAS8	3/8" – 1"	#8	100	1000

SDS Carbide-Tipped Drill Bits

These carbide-tipped drill bits feature a centering tip that allows exact hole placement and greatly reduces bit walking. A large relief cut in the fluting below the carbide reduces friction during dust removal, reducing heat and increasing bit life. Box fluting decreases vibration back into the tool and increases operator comfort during drilling.

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry
- ▶ Hollow Masonry
- ▶ Wallboard/Drywall



SDS-plus® Carbide-Tipped Drill Bits

Catalog No.	Drill Bit Size (in.)	Overall Length (in.)	Usable Length (in.)	Quantity
SDS5324	5/32 x 4	4	2	1
SDS5326	5/32 x 6	6	4	1
SDS3164	3/16 x 4	4	2	1
SDS3166	3/16 x 6	6	4	1
SDS3168	3/16 x 8	8	6	1
SDS31612	3/16 x 12	12	10	1
SDS1440	1/4 x 4	4	2	1
SDS1460	1/4 x 6	6	4	1
SDS1480	1/4 x 8	8	6	1
SDS1411	1/4 x 11	11	9	1
SDS1420	1/4 x 20	20	18	1
SDS5166	5/16 x 6	6	4	1
SDS5168	5/16 x 8	8	6	1
SDS51612	5/16 x 12	12	10	1
SDS3860	3/8 x 6	6	4	1
SDS3880	3/8 x 8	8	6	1
SDS3812	3/8 x 12	12	10	1
SDS3818	3/8 x 18	18	16	1
SDS7166	7/16 x 6	6	4	1
SDS71612	7/16 x 12	12	10	1
SDS1260	1/2 x 6	6	4	1
SDS1280	1/2 x 8	8	6	1
SDS1210	1/2 x 10	10	8	1
SDS1212	1/2 x 12	12	10	1

continues on page 48

SDS Carbide-Tipped Drill Bits

SDS-plus[®] Carbide-Tipped Drill Bits

continued from page 47

Catalog No.	Drill Bit Size (in.)	Overall Length (in.)	Usable Length (in.)	Quantity
SDS1218	1/2 x 18	18	16	1
SDS1224	1/2 x 24	24	22	1
SDS9166	9/16 x 6	6	4	1
SDS91612	9/16 x 12	12	10	1
SDS5860	5/8 x 6	6	4	1
SDS5880	5/8 x 8	8	6	1
SDS5812	5/8 x 12	12	10	1
SDS5818	5/8 x 18	18	16	1
SDS5824	5/8 x 24	24	22	1
SDS3480	3/4 x 8	8	6	1
SDS3412	3/4 x 12	12	10	1
SDS3418	3/4 x 18	18	16	1
SDS3424	3/4 x 24	24	18	1
SDS7880	7/8 x 8	8	6	1
SDS7812	7/8 x 12	12	10	1
SDS7818	7/8 x 18	18	16	1
SDS1012	1 x 12	12	10	1
SDS1018	1 x 18	18	16	1

SDS-max[®] Cutter* Carbide-Tipped Drill Bits

Catalog No.	Drill Bit Size (in.)	Overall Length (in.)	Usable Length (in.)	Quantity
SDSMHQ1213	1/2 x 13 (2 cutter)	13	8	1
SDSMHQ1221	1/2 x 21 (2 cutter)	21	16	1
SDSMHQ91613	9/16 x 13 (2 cutter)	13	8	1
SDSMHQ91621	9/16 x 21 (2 cutter)	21	16	1
SDSMHQ5813	5/8 x 13 (4 cutter)	13	8	1
SDSMHQ5821	5/8 x 21 (4 cutter)	21	16	1
SDSMHQ3413	3/4 x 13 (4 cutter)	13	8	1
SDSMHQ3421	3/4 x 21 (4 cutter)	21	16	1
SDSMHQ3436	3/4 x 36 (4 cutter)	36	30	1
SDSMHQ7813	7/8 x 13 (4 cutter)	13	8	1
SDSMHQ7821	7/8 x 21 (4 cutter)	21	16	1
SDSMHQ1013	1 x 13 (4 cutter)	13	8	1
SDSMHQ1021	1 x 21 (4 cutter)	21	16	1
SDSMHQ1036	1 x 36 (4 cutter)	36	30	1
SDSMHQ11821	1-1/8 x 21 (4 cutter)	21	16	1
SDSMHQ11423	1-1/4 x 23 (4 cutter)	23	18	1
SDSMHQ13823	1-3/8 x 23 (4 cutter)	23	18	1
SDSMHQ11223	1-1/2 x 23 (4 cutter)	23	18	1
SDSMHQ13423	1-3/4 x 23 (4 cutter)	23	18	1

*Cutter makes bit rebar-resistant.

Carbide-Tipped Drill Bits



Hex Driver Carbide-Tipped Drill Bits

Catalog No.	Drill Bit Size (in.)	Overall Length (in.)	Usable Length (in.)	Quantity
SDSH5325	5/32 x 5	5	2	1
SDSH5327	5/32 x 7	7	4	1
SDSH3165	3/16 x 5	5	2	1
SDSH3167	3/16 x 7	7	4	1



Taper Carbide-Tipped Drill Bits

Catalog No.	Drill Bit Size (in.)	Overall Length (in.)	Usable Length (in.)	Quantity
TAP53232	5/32 x 3-1/2	3-1/2	2-1/4	1
TAP53242	5/32 x 4-1/2	4-1/2	2-1/2	1
TAP53252	5/32 x 5-1/2	5-1/2	3-3/4	1
TAP31632	3/16 x 3-1/2	3-1/2	2-1/4	1
TAP31642	3/16 x 4-1/2	4-1/2	2-1/2	1
TAP31652	3/16 x 5-1/2	5-1/2	3-3/4	1



Spline Carbide-Tipped Drill Bits

Catalog No.	Drill Bit Size (in.)	Overall Length (in.)	Usable Length (in.)	Quantity
SPL3810	3/8 x 10	10	5	1
SPL3813	3/8 x 13	13	8	1
SPL3816	3/8 x 16	16	11	1
SPL1210	1/2 x 10	10	5	1
SPL1213	1/2 x 13	13	8	1
SPL1216	1/2 x 16	16	11	1
SPL1222	1/2 x 22	22	17	1
SPL91613	9/16 x 13	13	8	1
SPL91616	9/16 x 16	16	11	1
SPL91622	9/16 x 22	22	17	1
SPL5810	5/8 x 10	10	5	1
SPL5813	5/8 x 13	13	8	1
SPL5816	5/8 x 16	16	11	1
SPL5822	5/8 x 22	22	17	1
SPL3410	3/4 x 10	10	5	1
SPL3413	3/4 x 13	13	8	1
SPL3416	3/4 x 16	16	11	1
SPL3422	3/4 x 22	22	17	1
SPL7816	7/8 x 16	16	11	1
SPL7822	7/8 x 22	22	17	1
SPL1016	1 x 16	16	11	1
SPL1022	1 x 22	22	17	1

POWER-Sert[™] Adhesive Insert Anchors

The POWER-Sert Adhesive Insert Anchor is a proprietary internally threaded insert designed for use with structural adhesive. Our unique undercut design requires less adhesive and a shallow embedment while providing superior holding values in a variety of materials. Our exclusive FRICTION-FIT[™] locks adhesive in place and allows immediate fastening of the fixture during cure time[†]. The POWER-Sert Adhesive Insert Anchor is the ultimate problem solver!

[†] FRICTION-FIT[™] without full epoxy cure is for light-duty, temporary holding only and produces far less than advertised ultimate holding values.

Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Solid Masonry

Materials

- ▶ Zinc-Plated Carbon Steel
- ▶ Type 304 Stainless Steel
- ▶ Type 316 Stainless Steel

**Zinc-Plated Carbon Steel**

Catalog No.	Thread Size (UNC)	Anchor Size (in.)	Box Quantity	Carton Quantity
PS2-14	1/4 - 20	5/16 x 1-9/16	100	800
PS2-56	5/16 - 18	7/16 x 2-3/8	100	800
PS2-38	3/8 - 16	1/2 x 2-3/4	50	400
PS2-12	1/2 - 13	5/8 x 3-11/16	25	200
PS2-58	5/8 - 11	7/8 x 5-3/4	10	80
PS2-34	3/4 - 10	1 x 6-1/2	5	40
PS2-1	1 - 8	1-1/2 x 8-1/2	5	15

**Type 304 Stainless Steel**

Catalog No.	Thread Size (UNC)	Anchor Size (in.)	Box Quantity	Carton Quantity
PSS-38	3/8 - 16	1/2 x 2-3/4	50	400
PSS-12	1/2 - 13	5/8 x 3-11/16	25	200

**Type 316 Stainless Steel**

Catalog No.	Thread Size (UNC)	Anchor Size (in.)	Box Quantity	Carton Quantity
PS6-14	1/4 - 20	5/16 x 1-9/16	100	800
PS6-56	5/16 - 18	7/16 x 2-3/8	100	800
PS6-38	3/8 - 16	1/2 x 2-3/4	50	400
PS6-12	1/2 - 13	5/8 x 3-11/16	25	200
PS6-58	5/8 - 11	7/8 x 5-3/4	10	80
PS6-34	3/4 - 10	1 x 6-1/2	5	40
PS6-1	1 - 8	1-1/2 x 8-1/2	5	15

Inject-TITE™ (AWF) All-Weather Formula

The Inject-TITE (AWF) All Weather Formula is an acrylate anchoring system made for temperatures ranging from -15°F to 120°F. The AWF is a styrene-free formula that allows for use in a wide range of applications like bonding threaded rod and reinforcing bar hardware into drilled holes in solid (or hollow) concrete base materials. It won't shrink or sag, eliminating expansion forces and avoiding unwanted forces in the joint. It can be applied in wet or damp holes and can be used in areas with severe weather conditions.



Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Hollow Masonry
- ▶ Solid Masonry

Storage and Shelf Life

- ▶ The material should be stored at 40° - 95°F (5° - 35°C). Shelf life of properly stored, unopened containers is 12 months.

Compliance

- ▶ VOC-compliant. Styrene-free. Meets USDA specifications for use in food processing areas. ASTM C881, Types I, II*, IV and V*; Grade 3, Classes A, B & C (*except gel time).
- ▶ Contact us for list of DOT compliances and all other code approvals.



Inject-TITE (AWF) All-Weather Formula

Catalog No.	Description	Quantity	Carton Quantity
ECA8	9.3 fl. oz. (275 ml) Cartridge	1	12
ECA28	28 fl. oz. (825 ml) Cartridge	1	8

* Each adhesive tube is supplied with one nozzle

WARNING: NTSB safety recommendations prohibit the use of adhesive anchors in sustained overhead load-anchoring applications.

CAUTION: AWF epoxy is flammable. Keep away from heat, sparks and flame.

HEALTH	1
FLAMMABLE	3
REACTIVE.....	4

Inject-TITE™ (FS) Fast-Set Formula

The Inject-TITE (FS) Fast-Set Formula is a high-strength, two-part adhesive anchoring system. The FS is solvent-free and allows for use in a wide range of applications like bonding threaded rod and reinforcing bar hardware into drilled holes in solid (or hollow) concrete base materials. It won't shrink or sag, eliminating expansion forces and avoiding unwanted forces in the joint. It can be applied in wet or damp holes and can be used in areas with seismic concerns and severe weather conditions.



- Applications**
 - ▶ Normal Weight Concrete
 - ▶ Lightweight Concrete
 - ▶ Hollow Masonry
 - ▶ Solid Masonry
- Storage and Shelf Life**
 - ▶ The material should be stored above 50°F (10°C). Shelf life of properly stored, unopened containers is 24 months.

- Compliance**
 - ▶ VOC-compliant. Meets USDA specifications for use in food processing areas. ASTM C881, Types I, II*, IV, V*; Grade 3, Classes B and C (*except gel time).
 - ▶ Contact us for list of DOT compliances and all other code approvals.



Inject-TITE (FS) Fast-Set Formula			
Catalog No.	Description	Quantity	Carton Quantity
ECT8F	8.5 fl. oz. (250 ml) Cartridge	1	12
ECT22F	20.5 fl. oz. (600 ml) Cartridge	1	12

* Each adhesive tube is supplied with one nozzle

WARNING: NTSB safety recommendations prohibit the use of adhesive anchors in sustained overhead load-anchoring applications.

HEALTH	3
FLAMMABLE	1
REACTIVE.....	2

Inject-TITE™ (ST) Standard-Set Formula

The Inject-TITE (ST) Standard-Set Formula is a high-strength two-part adhesive anchoring system. The ST is solvent-free and allows for use in a wide range of applications like bonding threaded rod and reinforcing bar hardware into drilled holes in solid (or hollow) concrete base materials. It won't shrink or sag, eliminating expansion forces and avoiding unwanted forces in the joint. It can be applied in wet or damp holes and can be used in areas with severe weather conditions.



Applications

- ▶ Normal Weight Concrete
- ▶ Lightweight Concrete
- ▶ Hollow Masonry
- ▶ Solid Masonry

Storage and Shelf Life

- ▶ The material should be stored at 40° - 95°F (5° - 35°C). Shelf life of properly stored, unopened containers is 24 months.

Compliance

- ▶ VOC-compliant. Meets USDA specifications for use in food processing areas. ASTM C881 , Types I, II, IV, V Grade 3, Classes B and C.
- ▶ Contact us for list of DOT compliances and all other code approvals.



Inject-TITE (ST) Standard-Set Formula

Catalog No.	Description	Quantity	Carton Quantity
ECT22	20.5 fl. oz. (600 ml) Cartridge	1	12

* Each adhesive tube is supplied with one nozzle

WARNING: NTSB safety recommendations prohibit the use of adhesive anchors in sustained overhead load-anchoring applications.

HEALTH	3
FLAMMABLE	1
REACTIVE.....	2

Adhesive Accessories



Break-Off Mixing Nozzles

Catalog No.	Description	Box Quantity	Carton Quantity
ECTNZ12	Universal Nozzle	4	16



Dispensing Tools

Catalog No.	Description	Quantity
EHT10	For 8.5 fl. oz. and 9.3 fl. oz. Cartridges	1
EHT22	For 20.5 fl. oz. Cartridges	1
EHT28	For 28 fl. oz. Cartridges	1

*Color of dispensing tool subject to change



Nylon Screen Tubes

Catalog No.	Screen Size (in.)	Rod Dia. (in.)	Drill Bit Size (in.)	Quantity
ESCN3814	3/8 x 14	3/8	1/2	1
ESCN1214	1/2 x 14	1/2	5/8	1
ESCN5814	5/8 x 14	5/8	3/4	1
ESCN3414	3/4 x 14	3/4	7/8	1

*Special plastic allows tube to be cut to desired length

Adhesive Accessories



Stainless Steel Screen Tubes

Catalog No.	Screen Size (in.)	Rod Dia. (in.)	Drill Bit Size (in.)	Quantity
ESCS3832	3/8 x 3-1/2	3/8	1/2	1
ESCS3860	3/8 x 6	3/8	1/2	1
ESCS3810	3/8 x 10	3/8	1/2	1
ESCS1232	1/2 x 3-1/2	1/2	5/8	1
ESCS1260	1/2 x 6	1/2	5/8	1
ESCS1210	1/2 x 10	1/2	5/8	1
ESCS5860	5/8 x 6	5/8	3/4	1
ESCS5810	5/8 x 10	5/8	3/4	1
ESCS3410	3/4 x 10	3/4	7/8	1
ESCS3413	3/4 x 13	3/4	7/8	1



Stud Assemblies: Straight Cut*

Catalog Number			Stud Size (in.)	Box Quantity	Carton Quantity
Carbon Grade 2	Stainless Steel				
	304	316			
CS238-S	CSS38-S	CS638-S	3/8 x 5	50	300
CS212-S	CSS12-S	CS612-S	1/2 x 6-1/4	25	150
CS258-S	CSS58-S	CS658-S	5/8 x 7-1/2	10	60
CS234-S	CSS34-S	CS634-S	3/4 x 9-1/2	10	40
CS278-S	CSS78-S	CS678-S	7/8 x 10-1/4	5	20
CS210-S	CSS10-S	CS610-S	1 x 11-3/4	5	20
CS2114-S	CSS114-S	CS6114-S	1-1/4 x 14	5	20

*All stud assemblies are special order

####	Original Wej-It® Wedge Anchors	10
A	ALLIGATOR® All-Purpose Anchors, No Flange.....	38
AF	ALLIGATOR All-Purpose Anchors, With Flange	37
ASA	Sleeve-TITE™ Sleeve Anchors, Acorn Nut.....	11
ASAX	Sleeve-TITE Sleeve Anchors, Acorn Nut, Stainless Steel	13
AT	Ankr-TITE® Wedge Anchors, Zinc Plated	4
ATEZ	POWER-Skru™ Large Diameter Concrete Screws, Zinc-Plated	14
ATEZG	POWER-Skru, Mechanically Galvanized.....	15
ATG	Ankr-TITE Wedge Anchors, Hot-Dip Galvanized.....	6
ATS	Ankr-TITE Wedge Anchors, 304 Stainless Steel	7
ATSS	Ankr-TITE Wedge Anchors, 316 Stainless Steel	8
BA	SNAPTOGGLE® 3/16-24	34
BAL	SNAPTOGGLE 3/16-24, Long	35
BALS	SNAPTOGGLE 3/16-24, Long, Stainless Steel	35
BAS	SNAPTOGGLE 3/16-24, Stainless Steel	35
BB	SNAPTOGGLE 1/4-20	34
BBL	SNAPTOGGLE 1/4-20, Long.....	35
BBLS	SNAPTOGGLE 1/4-20, Long, Stainless Steel	35
BBS	SNAPTOGGLE 1/4-20, Stainless Steel	35
BC	SNAPTOGGLE 3/8-16.....	34
BCS	SNAPTOGGLE 3/8-16, Stainless Steel	35
BD	SNAPTOGGLE 1/2-13.....	34
BDS	SNAPTOGGLE 1/2-13, Stainless Steel	35
BE	SNAPTOGGLE 5/16-18	34
BM10	SNAPTOGGLE M10, Metric	35
BM10S	SNAPTOGGLE M10, Metric, Stainless Steel.....	35
BM5	SNAPTOGGLE M5, Metric.....	34
BM5L	SNAPTOGGLE M5, Metric, Long.....	35
BM5LS	SNAPTOGGLE M5, Metric, Long , Stainless Steel	35
BM5S	SNAPTOGGLE M5, Metric, Stainless Steel	35
BM6	SNAPTOGGLE M6, Metric.....	34
BM6L	SNAPTOGGLE M6, Metric, Long.....	35
BM6LS	SNAPTOGGLE M6, Metric, Long, Stainless Steel	35
BM6S	SNAPTOGGLE M6, Metric, Stainless Steel	35
BM8	SNAPTOGGLE M8, Metric.....	34
BM8S	SNAPTOGGLE M8, Metric, Stainless Steel	35
CCAT	Ankr-TITE CCAT Wedge Anchors Cat. 1 Cracked Concrete.....	9
CP	Strike-It™ Center Pin Anchors	28
CS2	Straight Cut Stud Asssemblies.....	55
CSA	Sleeve-TITE Sleeve Anchor, Rod Coupling Anchors	12
DES	Double Expansion Shields.....	25
DN	Nail-It™ Drive Nail Anchors	29
DNHS	Screw-In™ Drive Screw Anchor.....	30
DNS	Nail-It Drive Nail Anchors, Stainless Steel.....	29
DWAN	Self-Drilling Drywall Anchors, Plastic	46
DWAS	Self-Drilling Drywall Anchors, Metal	46
ECA	Inject-TITE™ AWF All-Weather Formula	51
ECT	Inject-TITE ST Standard-Set Formula.....	52
ECT##F	Inject-TITE FS Fast-Set Formula	53
ECTNZ	Break-Off Mixing Nozzles	54
EHT	Epoxy Gun	54
ESCN	Nylon Screen Tubes for Hollow Wall Applications.....	54
ESCS	Stainless Steel Screen Tubes for Brick and Block.....	55
FCS	Wej-Con® Concrete Screws, Phillips Flat Head.....	16
FCSS	Wej-Con Concrete Screws, Phillips Flat Head 410 Stainless Steel	17
FSA	Sleeve-TITE Sleeve Anchors, Flat Head	12
FSAX	Sleeve-TITE Sleeve Anchors, Flat Head Stainless Steel.....	13
HBSA	Sleeve-TITE Sleeve Anchor, Hex Bolt Head.....	12

HCS	Wej-Con® Concrete Screws, Slotted Hex Washer Head.....	17
HCSS	Wej-Con Concrete Screws, Hex Washer Head 410 Stainless Steel	18
HSA	Sleeve-TITE™ Sleeve Anchors, Hex Nut.....	11
HSAX	Sleeve-TITE Sleeve Anchors, Hex Nut Stainless Steel	13
HTCST	Hang-TITE™ Concrete Setting Tool	20
HTCV	Hang-TITE Concrete Vertical Hanger	20
HTSS	Hang-TITE Steel Side Hanger.....	20
HTSV	Hang-TITE Steel Vertical Hanger	20
HTWS	Hang-TITE Wood Side Hanger.....	19
HTWSST	Hang-TITE Universal Wood & Steel Setting Tool	20
HTWV	Hang-TITE Wood Vertical Hanger.....	19
HWL	Hollow Wall Anchors, Long	45
HWLD	Hollow Wall Drive Anchors, Long	45
HWS	Hollow Wall Anchors, Short	45
HWSD	Hollow Wall Drive Anchors, Short.....	45
HWXS	Hollow Wall Anchors, Extra Short	45
LSL	Lag Screw Shields, Long.....	26
LSS	Lag Screw Shields, Short.....	26
MS	Machine Screw Shields.....	27
PD	POWER-Drop™ Drop-In Anchors.....	24
PS2	POWER-Sert™ Adhesive Insert Anchors	50
PS6	POWER-Sert Adhesive Insert Anchors, 316 Stainless Steel	50
PSS	POWER-Sert Adhesive Insert Anchors, 304 Stainless Steel	50
SDF	Slam-It™ Split Drive Anchors, Flat Head	31
SDR	Slam-It Split Drive Anchors, Mushroom Head	31
SDS	SDS-plus® Carbide-Tipped Drill Bits.....	47
SDSH	Hex Driver Carbide-Tipped Drill Bits.....	49
SDSMHQ	SDS-max® Cutter Carbide-Tipped Drill Bits	48
SES	Single Expansion Shields	25
SP®	SnapSkru® Self-Drilling Drywall Anchors.....	36
SPL	Standard Spline Carbide-Tipped Drill Bits	49
SPM	MINI SnapSkru Self-Drilling Drywall Anchors	36
ST	Ultra-Drop™ Drop-In Anchor Setting Tool	22
STH	Hollo Set™ Setting Tool: Solid-Base Materials	23
STM	Ultra-Drop Drop-In Anchor Setting Tool, MINI	22
STSH	Hollo Set Setting Tool: Hollow-Base Materials	23
T35	TOGGLER® Plastic Toggle Anchors: 1-3/8" Grip.....	40
T39	TOGGLER Plastic Toggle Anchors: 1-1/2" Grip.....	40
TA®	TOGGLER Plastic Toggle Anchors: Hollow-Core Door, 1/8"-1/4"	39
TAP	Taper Drill Bits For Wej-Con Concrete Screws	49
TB®	TOGGLER Plastic Toggle Anchors: Residential Drywall, 3/8"-1/2"	39
TBM	Standard Wing Toggles.....	44
TBS1	TOGGLER Specialty Anchors: Shelving	41
TBS2	TOGGLER Specialty Anchors: Pegboard.....	42
TBW	TOGGLER Specialty Anchors: Wire Shelf.....	42
TC®	TOGGLER Plastic Toggle Anchors: Commercial Drywall, 5/8"-3/4" ...	40
TD	TOGGLER Plastic Toggle Anchors: Double Drywall	40
TH®	TOGGLER Specialty Anchors: Picture Hook.....	41
WD	Ultra-Drop Drop In Anchors, Standard	21
WDCT	Ultra-Drop Drop-In Anchors, Coil Thread	21
WDHS	Hollo Set Drop-In Anchors	23
WDL	Ultra-Drop Drop-In Anchors, Lipped Steel.....	21
WDM	Ultra-Drop Drop-In Anchors, MINI.....	22
WDS	Ultra-Drop Drop-In Anchors, 304 Stainless Steel	22
WDSS	Ultra-Drop Drop-In Anchors, 316 Stainless Steel.....	22
WTSA	Tie-Wire Sleeve Anchors	12
WTW	Tie-Wire Wedge Anchors	5

Notes

[illegible]

PRODUCT WARRANTY STATEMENT:

Mechanical Plastics Corp., in its sole discretion and option, will repair, replace or refund the original purchase price of the product for a period of 6 months from the date of sale by Mechanical Plastics Corp. or its distributors provided that the product contains a defect in material or workmanship, excluding normal wear and tear.

This warranty statement does not apply to any products not installed or used in compliance with the published instructions, proper and specific installment procedures, modifications to the product, defective materials to which the product is attached or which have deteriorated, use in conjunction with other manufacturers' anchors, acts of war, acts of terrorism, Force Majeure or any other extraordinary events.

NOTIFICATION:

Absence the receipt of notification by Mechanical Plastics Corp. of any such defect within the 6 months period shall constitute a waiver of any and all claims with regard to such product and sale.

LIMITATION OF LIABILITY:

To the extent permitted by law, the foregoing warranty is expressly in lieu of any and all other warranties, whether express or implied, including but not limited to the implied warranty of fitness for a particular purchase and the implied warranty of merchantability, and whether by statute, case law or otherwise. This warranty is the sole warranty provided by Mechanical Plastics Corp. No warranty is given in respect to the modification or improper installation of any product.

LIMITATION OF DAMAGES:

In no event shall Mechanical Plastics Corp. (including but not limited to its agents, directors, employees, managers, members, officers, representatives or shareholders) be liable to any entity, individual, organization or person for any lost income, lost opportunities, lost profits, lost savings, capital costs, or for any direct or indirect damages, or for any special or punitive damages, or for any consequential or incidental damages including but not limited to costs and attorney fees arising out of or related to the sale, use or inability to use the product whether based on contract, tort, warranty or other equitable or legal grounds.

INDEMNIFICATION:

Purchaser and/or customer hereby agrees to defend, indemnify and hold harmless Mechanical Plastics Corp. for any and all claims by any entity, person or third party for any damages, losses, special losses, punitive claims, or other claims and any consequential costs, including but not limited to legal costs and attorneys' fees.

ACCEPTANCE OF TERMS:

Purchase of any product from Mechanical Plastics Corp. is evidence of acceptance of these warranty terms by the purchaser.

**SAFETY, INSTALLATION, TECHNICAL, AND
CODE COMPLIANCE INFORMATION:**

For full up-to-date information on safety standards, installation instructions, technical specifications, code compliance and approvals, please visit **www.wejit.com**.

TOGGLER®

HIGH-PERFORMANCE ANCHORS®

wej-it®

HIGH-PERFORMANCE ANCHORS

Divisions of Mechanical Plastics Corp.

110 Richards Avenue • Norwalk, CT 06854

Call us:
(203) 857-2200

Fax: 203-857-2201 • E-mail: sales@wej-it.com
www.toggler.com • www.wej-it.com

Pound-It™, Hang-TITE™, Ankr-TITE®, Wej-It®, Sleeve-TITE™, Hollo Set™, Strike-It™, Nail-It™, Slam-It™, Screw-In™, POWER-Skru™, Wej-Con®, POWER-Drop™, Ultra-Drop™, TOGGLER®, TA®, TB®, TC®, TH®, TD™, T35™, T39™, SNAPTOGGLE®, SnapSkru®, ALLIGATOR®, POWER-Sert™, Inject-TITE™, Slam-TITE™, R-Blocker™, High-Performance Anchors®, BA™, BB™, BC™, BD™, BE™, BAL™, BBL™, BAS™, BBS™, BCS™, BDS™, BES™, BALS™, BBLS™, BM5™, BM6™, BM8™, BM10™, BM5L™, BM6L™, BM5S™, BM6S™, BM8S™, BM10S™, BM5LS™, BM6LS™, SP®, SPM™, A5™, A6™, A8™, A10™, AF5™, AF6™, AF8™, TBW™, TBS1™, TBS2™ are trademarks of Mechanical Plastics Corp.

ClosetMaid® is a registered trademark of the ClosetMaid Corporation, a subsidiary of Emerson Electric Co.

SDS-max® and SDS-plus® are registered trademarks of Robert Bosch GmbH.